



| Characteristics | Mirage Classic |
|---|--|
| | Flair Collection - Character |
| Description | <ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) • An ultra-matte finish on a character grade |
| Thickness | 3/4" (19 mm) |
| Length | • Random lengths (from 10" (250 mm) to 76" (1,930 mm)) |
| Width | 4-1/4" (108 mm) |
| Species | 3 species: Red Oak Character, White Oak Character, plain sawn, Maple Character |
| Grade | <ul style="list-style-type: none"> • Character : These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. |
| Color choice <small>(refer to 2017 Mirage Collections)</small> | 5 colors (Maple): Snowdrift, Sand Dune, Grey Drizzle, Dark Leaf, Nightfall 1 color (Red Oak): Nightfall 5 colors (White Oak, plain sawn): White Mist, Snowdrift, Sand Dune, Grey Drizzle, Dark Leaf |
| Finish | DuraMatt™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Formaldehyde: Free Water and solvent: No trace Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55 |
| Applicable standards | Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 • Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): R value: R 0.6 to 0.8 (depends on wood species) 0.25 to 0.40 watt/cm ² (depends on wood species) |
| Installation | Nailed or stapled down (above and on grade) |
| Subfloor | Wood |
| Provenance | Made in St-Georges, Qc, Canada. |
| Use | Residential or light commercial |
| Accessory | Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round |
| Warranty | <ul style="list-style-type: none"> • Structural lifetime limited warranty • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications |
| Packaging | 4-1/4" (108 mm) |
| Content of a box | • 18 ft ² (1.672 m ²) |
| Size of a box | • 85-1/2" L x 9" W x 3-1/4" H |
| Weight of a box | • 45 to 55 lbs |
| Content of a pallet | • 48 boxes = 864 ft ² (4 boxes/W x 12 boxes/H) |
| Size of a pallet | • 85-1/2" L x 38" W x 43" H |
| Relative species hardness | |
| NWFA Janka Test | <ul style="list-style-type: none"> • Red Oak 1,290 lbs - average hardness • White Oak, plain sawn 1,360 lbs - 5% harder • Maple 1,450 lbs - 12% harder |
| Hardness test (ASTM-D-143) | |
| Red Oak 1290 lbs* - 100% | |
| *lbs = Applied force in pounds | |