



Characteristics	Mirage Classic	
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) 	
Thickness	3/4"	
Width	3-1/4"	4-1/4"
Length ¹	Random lengths from 10" (250 mm) to 76" (1,930 mm)	
Installation	Nailed or stapled down (above and on grade)	
Subfloor	Wood	
Species	3 species: Maple, Red Oak, White Oak	
Grade	<ul style="list-style-type: none"> • Select & Better: Selection of more uniform wood grain with slight variations in natural shading. • Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. • ▲ Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 	
Color choice <i>(refer to 2023 Mirage Collections)</i>	Some products may not be available. Ask your Mirage representative or consult the Product Chart .	
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> • DuraMatt® (5% gloss) • Nanolinx® HD <ul style="list-style-type: none"> • Cashmere®* (18% gloss) • Nanolinx® Commercial (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5	
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species)	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) R value: R 0.6 to 0.8 (depends on wood species)
Provenance	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Classic) conform Made in St-Georges, Qc, Canada.	
Use	Residential, light commercial or commercial (Nanolinx® Commercial)	
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 35% and 55%). 	<ul style="list-style-type: none"> • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications • 5-year finish warranty for commercial applications with Nanolinx® Commercial
Packaging	3-1/4"	4-1/4"
Content of a box	20 sq. ft.	18 sq. ft.
Size of a box	79" L x 10-1/2" W x 3-1/4" H	85-1/2" L x 9" W x 3-1/4" H
Weight of a box	49 to 60 lbs	45 to 55 lbs
Content of a pallet	48 boxes = 960 sq. ft. (4 boxes/W x 12 boxes/H)	48 boxes = 864 sq. ft. (4 boxes/W x 12 boxes/H)
Size of a pallet	79" L x 42" W x 42" H	85-1/2" L x 36" W x 42" H
Relative species hardness		
NWFA Janka Test	• Red Oak	1,290 lbs - average hardness
Hardness test (ASTM-D-143)	• White Oak	1,360 lbs - 5% harder
	• Maple	1,450 lbs - 12% harder
Red Oak 1290 lbs* - 100% *lbs = Applied force in pounds		

* Cashmere is a registered trademark used under license.

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.



Characteristics	Mirage Engineered	
Description	<ul style="list-style-type: none"> Engineered prefinished hardwood flooring with tongues and grooves Micro-V bevel (on 4 sides) 	
Thickness	1/2" (Sawn hardwood layer 5/32", 7-ply plywood base 11/32")	
Width	5"	7"
Length ¹	Lengths from 20" (511 mm) to 82" (2,086 mm)	
Installation	Nailed, stapled or glued (above, on or below grade)	
Subfloor	Wood, concrete or radiant heat system	
Species	3 species: Maple, Red Oak, Oak	
Grade	<ul style="list-style-type: none"> Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 	
Color choice (refer to 2023 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart .	
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane.	
	<ul style="list-style-type: none"> DuraMatt[®] X (10% gloss) Nanolinx[®] HD <ul style="list-style-type: none"> Cashmere[®]* (18% gloss) Nanolinx[®] Commercial (18% gloss) 	
	UV Protection: All products	
Applicable standards	Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5	
	Surface Burning (ASTM-E-84):	
	<ul style="list-style-type: none"> FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) SD (Smoke Development) < 400 (depends on wood species) 	
	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSV (Flame Spread Value) 80 (depends on wood species) SD (Smoke Development) < 350 (depends on wood species) 	
Provenance	Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm ² (depends on wood species)	
	R value: R 0.44 to 0.48 (depends on wood species)	
	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Engineered) conform	
Use	Made in St-Georges, Qc, Canada.	
Accessory	Residential, light commercial or commercial (Nanolinx [®] Commercial)	
Warranty	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round	
	Acoustitech underlayments are recommended by Mirage. To know more about the minimum criteria needed regarding the recommended waterproof acoustic underlayment, please refer to the Technical Newsletter #20 in the Guides and Support section at miragefloors.com .	
Packaging	5"	7"
	Content of a box Size of a box Weight of a box Content of a pallet Size of a pallet	<ul style="list-style-type: none"> 34.10 sq. ft. 83" L x 10-1/2" W x 3-1/4" H 65 to 70 lbs 32 boxes = 1,091.20 sq. ft. (4 boxes/W x 8 boxes/H) 83" L x 42" W x 30" H
Relative species hardness		
NWFA Janka Test Hardness test (ASTM-D-143)	<ul style="list-style-type: none"> Red Oak Oak Maple 	<ul style="list-style-type: none"> 1,290 lbs - average hardness 1,290 lbs - average hardness 1,450 lbs - 12% harder
Red Oak 1,290 lbs* - 100% *lbs = Applied force in pounds		

* Cashmere is a registered trademark used under license.

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.



Characteristics	Mirage Lock		
Description	<ul style="list-style-type: none"> • Lock prefinished hardwood flooring • 2G™ angling system on the long side of the board of all widths • 5G* Fold Down system on the short side of the board of 6-1/2" width • Incomparable tongue and groove fit for remarkable uniformity • Micro-V bevel (on 4 sides) 		
Thickness	7/16" (Sawn hardwood layer 1/16", HDF Core 9/32" and wood backing board)		
Width	4-5/16" 	5" 	6-1/2"  
Length ¹	Lengths from 14" (350 mm) to 46" (1,172 mm)	Lengths from 17" (422 mm) to 69" (1,752 mm)	Lengths from 22" (570 mm) to 69" (1,752 mm)
Installation	Floated over a recommended underlayment or glued down (above, on or below grade)		
Subfloor	Wood, concrete or radiant heat system		
Species	3 species: Maple, Red Oak, White Oak		
Grade	<ul style="list-style-type: none"> • Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. • Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 		
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> • DuraMatt® (5% gloss) • Nanolinx® HD <ul style="list-style-type: none"> • Cashmere* (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5		
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 85 to 110 • Class C (depends on wood species) • SD (Smoke Development) 220 to 240 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.46 to 0.47 watt/cm ² (depends on wood species) R value: R 0.34 to 0.36 (depends on wood species) Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Lock) conform		
Provenance	Made in St-Georges, Qc, Canada.		
Use	Residential or light commercial		
Accessories	Round Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round, Round Stair Nosing for glued installation, Round Reducer for glued installation and underlayment. Acoustitech underlayments are recommended by Mirage. To know more about the minimum criteria needed regarding the recommended waterproof acoustic underlayment, please refer to the Technical Newsletter #20 in the Guides and Support section at miragefloors.com .		
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 30% and 60%). • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications 		
Packaging	4-5/16"	5"	6-1/2"
Content of a box	• 22 sq. ft.	• 32.60 sq. ft.	• 24.35 sq. ft.
Size of a box	• 48" L x 9-1/2" W x 3-3/4" H	• 71" L x 10-3/4" W x 3-3/4" H	• 71" L x 7-1/2" W x 3-3/4" H
Weight of a box	• 40 to 42 lbs	• 60 to 62 lbs	• 45 to 47 lbs
Content of a pallet	• 40 boxes = 880 sq. ft.	• 36 boxes = 1,173.60 sq. ft.	• 48 boxes = 1,168.80 sq. ft.
Size of a pallet	(4 boxes/W x 10 boxes/H) • 48" L x 38" W x 40" H	(4 boxes/W x 9 boxes/H) • 71" L x 43" W x 36" H	(6 boxes/W x 8 boxes/H) • 71" L x 45" W x 32" H
Relative species hardness	NWFA Janka Test Hardness test (ASTM-D-143) <ul style="list-style-type: none"> • Red Oak 1,290 lbs - average hardness • White Oak 1,360 lbs - 5% harder • Maple 1,450 lbs - 12% harder Red Oak 1,290 lbs* - 100% *lbs = Applied force in pounds		

* Cashmere is a registered trademark used under license.

** 2G™ and 5G* are patented technologies invented by Välinge Innovation AB. The 2G™ and 5G* word marks and logos are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.



Characteristics	Mirage TruBalance																	
Description	<ul style="list-style-type: none"> Structured prefinished hardwood flooring Incomparable tongue and groove fit for remarkable uniformity Micro-V bevel (on 4 sides) 																	
Thickness	3/4" (Sawn hardwood layer 5/32", SPF Quarter sawn core layer 17/32" and wood backing board 1/16")																	
Width	5"	6-1/2"	7-3/4"															
Length ¹	Lengths from 20" (511 mm) to 82" (2,086 mm)		Lengths from 23" (590 mm) to 82" (2,086 mm)															
Installation	Nailed, stapled, glued down or floated installation** (above, on or below grade)																	
Subfloor	Wood, concrete or radiant heat system																	
Species	5 species: Maple, Red Oak, White Oak, Hickory, Walnut																	
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. ⚠️ Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 																	
Color choice (refer to 2023 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart .																	
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) Nanolinx® HD <ul style="list-style-type: none"> Cashmere® (18% gloss) Nanolinx® Commercial (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5																	
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 90 Class C SD (Smoke Development) 80 Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSR (Flame Spread Rating) 107 SDC (Smoke Development Classification) 311 Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm ² (depends on wood species)																	
Provenance	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (TruBalance) conform Made in St-Georges, Qc, Canada.																	
Use	Residential, light commercial or commercial																	
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round Acoustitech underlayments are recommended by Mirage. To know more about the minimum criteria needed regarding the recommended waterproof acoustic underlayment, please refer to the Technical Newsletter #20 in the Guides and Support section at miragefloors.com .																	
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (For the glued down and nailed/stapled installation relative humidity must be maintained within a range of 25% and 80%. For the floated installation relative humidity must be maintained between 30% and 60%). 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 																	
Packaging	5"	6-1/2"	7-3/4"															
Content of a box	• 22.70 sq. ft.	• 14.75 sq. ft.	• 17.60 sq. ft.															
Size of a box	• 83" L x 10-1/2" W x 3-1/4" H	• 83" L x 7" W x 3-1/4" H	• 83" L x 8-1/4" W x 3-1/4" H															
Weight of a box	• 42 to 45 lbs	• 27 to 31 lbs	• 32 to 36 lbs															
Content of a pallet	• 48 boxes = 1,089.60 sq. ft. (4 boxes/W x 12 boxes/H)	• 72 boxes = 1,062.00 sq. ft. (6 boxes/W x 12 boxes/H)	• 60 boxes = 1,056.00 sq. ft. (5 boxes/W x 12 boxes/H)															
Size of a pallet	• 83" L x 42" W x 42" H	• 83" L x 42" W x 42" H	• 83" L x 42" W x 42" H															
Relative species hardness	<table border="0"> <tr> <td>NWFA Janka Test</td> <td>• Walnut</td> <td>1,010 lbs - 22% softer</td> </tr> <tr> <td>Hardness test (ASTM-D-143)</td> <td>• Red Oak</td> <td>1,290 lbs - average hardness</td> </tr> <tr> <td></td> <td>• White Oak</td> <td>1,360 lbs - 5% harder</td> </tr> <tr> <td>Red Oak 1,290 lbs* - 100%</td> <td>• Maple</td> <td>1,450 lbs - 12% harder</td> </tr> <tr> <td>*lbs = Applied force in pounds</td> <td>• Hickory</td> <td>1,820 lbs - 41% harder</td> </tr> </table>			NWFA Janka Test	• Walnut	1,010 lbs - 22% softer	Hardness test (ASTM-D-143)	• Red Oak	1,290 lbs - average hardness		• White Oak	1,360 lbs - 5% harder	Red Oak 1,290 lbs* - 100%	• Maple	1,450 lbs - 12% harder	*lbs = Applied force in pounds	• Hickory	1,820 lbs - 41% harder
NWFA Janka Test	• Walnut	1,010 lbs - 22% softer																
Hardness test (ASTM-D-143)	• Red Oak	1,290 lbs - average hardness																
	• White Oak	1,360 lbs - 5% harder																
Red Oak 1,290 lbs* - 100%	• Maple	1,450 lbs - 12% harder																
*lbs = Applied force in pounds	• Hickory	1,820 lbs - 41% harder																

* Cashmere is a registered trademark used under license.

** For floated installation, please review the [TruBalance installation Guide](#) available on Mirage website in the [Guides and support section](#).

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.



Characteristics	Mirage TruBalance										
	Herringbone										
Description	<ul style="list-style-type: none"> Structured prefinished hardwood flooring Micro-V bevel (on 4 sides) Incomparable tongue and groove fit for remarkable uniformity 										
Thickness	3/4" (Sawn hardwood layer 5/32", SPF Quarter sawn core layer 17/32" and wood backing board 1/16")										
Width	5" (127 mm)										
Length ¹	20" (508 mm)										
Installation	Glued down (above, on or below grade)										
Subfloor	Wood, concrete or radiant heat system										
Species	5 species: Maple, Red Oak, White Oak, Hickory, Walnut										
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. ▲ Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 										
Color choice <i>(refer to 2023 Mirage Collections)</i>	Some products may not be available. Ask your Mirage representative or consult the Product Chart .										
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) Nanolinx® HD <ul style="list-style-type: none"> Cashmere* (18% gloss) Nanolinx® Commercial (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5										
Applicable standards	<table border="0"> <tr> <td> Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 90 Class C • SD (Smoke Development) 80 </td> <td> Surface Burning (ULC-S-102-2): • FSR (Flame Spread Rating) 107 • SDC (Smoke Development Classification) 311 </td> </tr> </table> Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm ² (depends on wood species) Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (TruBalance) conform	Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 90 Class C • SD (Smoke Development) 80	Surface Burning (ULC-S-102-2): • FSR (Flame Spread Rating) 107 • SDC (Smoke Development Classification) 311								
Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 90 Class C • SD (Smoke Development) 80	Surface Burning (ULC-S-102-2): • FSR (Flame Spread Rating) 107 • SDC (Smoke Development Classification) 311										
Provenance	Made in St-Georges, Qc, Canada.										
Use	Residential, light commercial or commercial										
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round Acoustitech underlayments are recommended by Mirage. To know more about the minimum criteria needed regarding the recommended waterproof acoustic underlayment, please refer to the Technical Newsletter #20 in the Guides and Support section at miragefloors.com .										
Warranty	<table border="0"> <tr> <td> <ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must be maintained within a range of 25% and 80%). </td> <td> <ul style="list-style-type: none"> 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial </td> </tr> </table>	<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must be maintained within a range of 25% and 80%). 	<ul style="list-style-type: none"> 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 								
<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must be maintained within a range of 25% and 80%). 	<ul style="list-style-type: none"> 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 										
Patterns	<table border="0"> <tr> <td> <ul style="list-style-type: none"> Herringbone Basket Double Herringbone </td> <td> <ul style="list-style-type: none"> Cube English pattern (bricks) Fence </td> </tr> </table>	<ul style="list-style-type: none"> Herringbone Basket Double Herringbone 	<ul style="list-style-type: none"> Cube English pattern (bricks) Fence 								
<ul style="list-style-type: none"> Herringbone Basket Double Herringbone 	<ul style="list-style-type: none"> Cube English pattern (bricks) Fence 										
Packaging	5"										
Content of a box	16.67 sq. ft.										
Size of a box	61-1/4" L x 10-1/2" W x 3-1/4" H										
Weight of a box	28 to 32 lbs										
Content of a pallet	48 boxes = 800.16 sq. ft. (4 boxes/W x 12 boxes/H)										
Size of a pallet	61-1/4" L x 42" W x 42" H										
Relative species hardness	<table border="0"> <tr> <td>• Walnut</td> <td>1,010 lbs - 22% softer</td> </tr> <tr> <td>• Red Oak</td> <td>1,290 lbs - average hardness</td> </tr> <tr> <td>• White Oak</td> <td>1,360 lbs - 5% harder</td> </tr> <tr> <td>• Maple</td> <td>1,450 lbs - 12% harder</td> </tr> <tr> <td>• Hickory</td> <td>1,820 lbs - 41% harder</td> </tr> </table> Red Oak 1,290 lbs* - 100% *lbs = Applied force in pounds	• Walnut	1,010 lbs - 22% softer	• Red Oak	1,290 lbs - average hardness	• White Oak	1,360 lbs - 5% harder	• Maple	1,450 lbs - 12% harder	• Hickory	1,820 lbs - 41% harder
• Walnut	1,010 lbs - 22% softer										
• Red Oak	1,290 lbs - average hardness										
• White Oak	1,360 lbs - 5% harder										
• Maple	1,450 lbs - 12% harder										
• Hickory	1,820 lbs - 41% harder										



Characteristics	Mirage TruBalance						
	Chevron						
Description	<ul style="list-style-type: none"> Structured prefinished hardwood flooring Micro-V bevel (on 4 sides) Incomparable tongue and groove fit for remarkable uniformity 						
Thickness	3/4" (Sawn hardwood layer 5/32", SPF Quarter sawn core layer 17/32" and wood backing board 1/16")						
Width	5" (127 mm)						
Length ¹	24-7/16" (620 mm)						
Installation	Glued down (above, on or below grade)						
Subfloor	Wood, concrete or radiant heat system						
Species	1 species: White Oak						
Grade	<ul style="list-style-type: none"> Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 						
Color choice (refer to 2023 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart .						
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5						
Applicable standards	<table border="0"> <tr> <td> Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 90 Class C • SD (Smoke Development) 80 </td> <td> Surface Burning (ULC-S-102-2): • FSR (Flame Spread Rating) 107 • SDC (Smoke Development Classification) 311 </td> </tr> <tr> <td colspan="2"> Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm² (depends on wood species) </td> </tr> <tr> <td colspan="2"> Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (TruBalance) conform </td> </tr> </table>	Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 90 Class C • SD (Smoke Development) 80	Surface Burning (ULC-S-102-2): • FSR (Flame Spread Rating) 107 • SDC (Smoke Development Classification) 311	Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm ² (depends on wood species)		Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (TruBalance) conform	
Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 90 Class C • SD (Smoke Development) 80	Surface Burning (ULC-S-102-2): • FSR (Flame Spread Rating) 107 • SDC (Smoke Development Classification) 311						
Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm ² (depends on wood species)							
Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (TruBalance) conform							
Provenance	Made in St-Georges, Qc, Canada.						
Use	Residential, light commercial or commercial						
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round Acoustitech underlayments are recommended by Mirage. To know more about the minimum criteria needed regarding the recommended waterproof acoustic underlayment, please refer to the Technical Newsletter #20 in the Guides and Support section at miragefloors.com .						
Warranty	<table border="0"> <tr> <td> <ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must be maintained within a range of 25% and 80%). </td> <td> <ul style="list-style-type: none"> 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial </td> </tr> </table>	<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must be maintained within a range of 25% and 80%). 	<ul style="list-style-type: none"> 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 				
<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must be maintained within a range of 25% and 80%). 	<ul style="list-style-type: none"> 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 						
Recommended	For the installation of Chevron flooring, we recommend maintaining the relative humidity within a range of 35% and 70%. Staying in this range will ensure the pattern and overall look of your floor last over the years. For more information on the installation of Chevron flooring, consult the Installation Guide.						
Patterns	<table border="0"> <tr> <td> <ul style="list-style-type: none"> Chevron Spearhead Brooklyn Bridge </td> <td> <ul style="list-style-type: none"> Leaf line Boardwalk </td> </tr> </table>	<ul style="list-style-type: none"> Chevron Spearhead Brooklyn Bridge 	<ul style="list-style-type: none"> Leaf line Boardwalk 				
<ul style="list-style-type: none"> Chevron Spearhead Brooklyn Bridge 	<ul style="list-style-type: none"> Leaf line Boardwalk 						
Packaging	5"						
Content of a box	• 13,60 sq. ft.						
Size of a box	• 61-1/4" L x 10-1/2" W x 3-1/4" H						
Weight of a box	• 23 to 26 lbs						
Content of a pallet	• 48 boxes = 652,80 sq. ft. (4 boxes/W x 12 boxes/H)						
Size of a pallet	• 61-1/4" L x 42" W x 42" H						
Relative species hardness							
NWFA Janka Test	• White Oak 1,360 lbs - 5% harder						
Hardness test (ASTM-D-143)							
Red Oak 1,290 lbs* - 100%							
*lbs = Applied force in pounds							

* Cashmere is a registered trademark used under license.

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.