



Characteristics	Mirage Classic	
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) 	
Thickness	3/4"	
Width	3-1/4"	4-1/4"
Length ¹	Random lengths from 10" (250 mm) to 76" (1,930 mm)	
Installation	Nailed or stapled down (above and on grade)	
Subfloor	Wood	
Species	3 species: Maple, Red Oak, White Oak	
Grade	<ul style="list-style-type: none"> • Select & Better: Selection of more uniform wood grain with slight variations in natural shading. • Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. • ▲ Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 	
Color choice (refer to 2022 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart .	
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> • DuraMatt[®] (5% gloss) • Nanolinx[®] HD <ul style="list-style-type: none"> • Cashmere[®]* (18% gloss) • Nanolinx[®] Commercial (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5	
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species)	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) R value: R 0.6 to 0.8 (depends on wood species)
	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Classic) conform	
Provenance	Made in St-Georges, Qc, Canada.	
Use	Residential, light commercial or commercial (Nanolinx [®] Commercial)	
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 35% and 55%). 	<ul style="list-style-type: none"> • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications • 5-year finish warranty for commercial applications with Nanolinx[®] Commercial
Packaging	3-1/4"	4-1/4"
Content of a box	• 20 sq. ft.	• 18 sq. ft.
Size of a box	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 sq. ft. (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 sq. ft. (4 boxes/W x 12 boxes/H)
Size of a pallet	• 79" L x 42" W x 42" H	• 85-1/2" L x 37" W x 42" H
Relative species hardness		
NWFA Janka Test	• Red Oak	1,290 lbs - average hardness
Hardness test (ASTM-D-143)	• White Oak	1,360 lbs - 5% harder
	• Maple	1,450 lbs - 12% harder
Red Oak 1290 lbs* - 100% *lbs = Applied force in pounds		

* Cashmere is a registered trademark used under license.

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.



Characteristics	Mirage Engineered			
Description	<ul style="list-style-type: none"> Engineered prefinished hardwood flooring with tongues and grooves Micro-V bevel (on 4 sides) 			
Thickness	1/2" (Sawn hardwood layer 5/32", 7-ply plywood base 11/32")			
Width	5" E-Escape & DreamVille	5"	6-1/2"	7"
Length ¹	Lengths from 17" (422 mm) to 69" (1,752 mm)		Lengths from 20" (511 mm) to 82" (2,086 mm)	
Installation	Nailed, stapled or glued (above, on or below grade)			
Subfloor	Wood, concrete or radiant heat system			
Species	3 species: Maple, Red Oak, White Oak			
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. ⚠ Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 			
Color choice (refer to 2022 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart .			
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt[®] (5% gloss) DuraMatt[®] X (10% gloss) Nanolinx[®] HD <ul style="list-style-type: none"> Cashmere[®] (18% gloss) Nanolinx[®] Commercial (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5			
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 100 to 150 <ul style="list-style-type: none"> Class C (depends on wood species) SD (Smoke Development) < 400 (depends on wood species) Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSV (Flame Spread Value) 80 (depends on wood species) SD (Smoke Development) < 350 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm ² (depends on wood species) R value: R 0.44 to 0.48 (depends on wood species) Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Engineered) conform			
Provenance	Made in St-Georges, Qc, Canada.			
Use	Residential, light commercial or commercial (Nanolinx [®] Commercial)			
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round			
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 25% and 70%). 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx[®] Commercial 			
Packaging	5" E-Escape & DreamVille	5"	6-1/2"	7"
Content of a box	• 28.50 sq. ft.	• 34.10 sq. ft.	• 22.15 sq. ft.	• 23.8 sq. ft.
Size of a box	• 70-3/4" L x 10-3/4" W x 3-1/4" H	• 83" L x 10-1/2" W x 3-1/4" H	• 83" L x 7" W x 3-1/4" H	• 83-1/2" L x 7-1/2" W x 3-1/4" H
Weight of a box	• 52 to 54 lbs	• 65 to 70 lbs	• 42 to 45 lbs	• 44 to 47 lbs
Content of a pallet	• 48 boxes = 1,368 sq. ft.	• 32 boxes = 1,091.2 sq. ft.	• 48 boxes = 1,063.2 sq. ft.	• 50 boxes = 1,190 sq. ft.
Size of a pallet	(4 boxes/W x 12 boxes/H) • 71" L x 43" W x 43" H	(4 boxes/W x 8 boxes/H) • 83" L x 42" W x 30" H	(6 boxes/W x 8 boxes/H) • 83" L x 42" W x 30" H	(5 boxes/W x 10 boxes/H) • 83-1/2" L x 37" W x 36-1/4" H
Relative species hardness				
NWFA Janka Test Hardness test (ASTM-D-143)	<ul style="list-style-type: none"> Red Oak White Oak Maple 	<ul style="list-style-type: none"> 1,290 lbs - average hardness 1,360 lbs - 5% harder 1,450 lbs - 12% harder 		
Red Oak 1,290 lbs* - 100% *lbs = Applied force in pounds				

* Cashmere is a registered trademark used under license.

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.






Characteristics	Mirage Engineered						
	Herringbone						
Description	<ul style="list-style-type: none"> Engineered prefinished hardwood flooring with tongue and groove edges, and grooves at both ends Micro-V bevel (on 4 sides) 						
Thickness	1/2" (Sawn hardwood layer 5/32", 7-ply plywood base 11/32")						
Width	5" (127 mm)						
Length ¹	20" (508 mm)						
Installation	Glued down (above, on or below grade)						
Subfloor	Wood, concrete or radiant heat system						
Species	3 species: Maple, Red Oak, White Oak						
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. ⚠ Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 						
Color choice (refer to 2022 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart .						
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) Nanolinx® HD <ul style="list-style-type: none"> Cashmere®* (18% gloss) Nanolinx® Commercial (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5						
Applicable standards	<table border="0"> <tr> <td> Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) SD (Smoke Development) < 400 (depends on wood species) </td> <td> Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSV (Flame Spread Value) 80 (depends on wood species) SD (Smoke Development) < 350 (depends on wood species) </td> </tr> <tr> <td> Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm² (depends on wood species) </td> <td> R value: R 0.44 to 0.48 (depends on wood species) </td> </tr> <tr> <td colspan="2"> Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Engineered) conform </td> </tr> </table>	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) SD (Smoke Development) < 400 (depends on wood species) 	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSV (Flame Spread Value) 80 (depends on wood species) SD (Smoke Development) < 350 (depends on wood species) 	Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm ² (depends on wood species)	R value: R 0.44 to 0.48 (depends on wood species)	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Engineered) conform	
Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) SD (Smoke Development) < 400 (depends on wood species) 	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSV (Flame Spread Value) 80 (depends on wood species) SD (Smoke Development) < 350 (depends on wood species) 						
Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm ² (depends on wood species)	R value: R 0.44 to 0.48 (depends on wood species)						
Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Engineered) conform							
Provenance	Made in St-Georges, Qc, Canada.						
Use	Residential, light commercial or commercial (Nanolinx® Commercial)						
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round						
Warranty	<table border="0"> <tr> <td> <ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 25% and 70%). </td> <td> <ul style="list-style-type: none"> 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial </td> </tr> </table>	<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 25% and 70%). 	<ul style="list-style-type: none"> 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 				
<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 25% and 70%). 	<ul style="list-style-type: none"> 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 						
Patterns	<table border="0"> <tr> <td> <ul style="list-style-type: none"> Herringbone Basket Double Herringbone </td> <td> <ul style="list-style-type: none"> Cube English pattern (bricks) Fence </td> </tr> </table>	<ul style="list-style-type: none"> Herringbone Basket Double Herringbone 	<ul style="list-style-type: none"> Cube English pattern (bricks) Fence 				
<ul style="list-style-type: none"> Herringbone Basket Double Herringbone 	<ul style="list-style-type: none"> Cube English pattern (bricks) Fence 						
Packaging	Length: 20"						
Content of a box	• 25 sq. ft.						
Size of a box	• 61" L x 10-1/2" W x 3-1/4" H						
Weight of a box	• 46 to 51 lbs						
Content of a pallet	• 40 boxes = 1,000 sq. ft. (4 boxes/W x 10 boxes/H)						
Size of a pallet	• 61" L x 42" W x 37" H						
Relative species hardness							
NWFA Janka Test	• Red Oak 1,290 lbs - average hardness						
Hardness test (ASTM-D-143)	• White Oak 1,360 lbs - 5% harder						
	• Maple 1,450 lbs - 12% harder						
Red Oak 1,290 lbs* - 100%							
*lbs = Applied force in pounds							

* Cashmere is a registered trademark used under license.

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.



Characteristics	Mirage Lock								
Description	<ul style="list-style-type: none"> • Lock prefinished hardwood flooring • 2G™ angling system on the long side of the board of all widths • 5G* Fold Down system on the short side of the board of 6-1/2" width • Incomparable tongue and groove fit for remarkable uniformity • Micro-V bevel (on 4 sides) 								
Thickness	7/16" (Sawn hardwood layer 1/16", HDF Core 9/32" and wood backing board)								
Width	4-5/16" 	5" 	6-1/2" 						
Length ¹	Lengths from 14" (350 mm) to 46" (1,172 mm)	Lengths from 17" (422 mm) to 69" (1,752 mm)	Lengths from 22" (570 mm) to 69" (1,752 mm)						
Installation	Floated over a recommended underlayment or glued down (above, on or below grade)								
Subfloor	Wood, concrete or radiant heat system								
Species	3 species: Maple, Red Oak, White Oak								
Grade	<ul style="list-style-type: none"> • Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. • Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 								
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> • DuraMatt® (5% gloss) • Nanolinx® HD <ul style="list-style-type: none"> • Cashmere* (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5								
Applicable standards	<table border="0"> <tr> <td> Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 85 to 110 Class C (depends on wood species) • SD (Smoke Development) 220 to 240 (depends on wood species) </td> <td> Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 85 to 90 (depends on wood species) • SD (Smoke Development) 305 to 365 (depends on wood species) </td> </tr> <tr> <td> Critical radiant flux (ASTM-E-648-94a): 0.46 to 0.47 watt/cm² (depends on wood species) </td> <td> R value: R 0.34 to 0.36 (depends on wood species) </td> </tr> <tr> <td colspan="2"> Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Lock) conform </td> </tr> </table>			Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 85 to 110 Class C (depends on wood species) • SD (Smoke Development) 220 to 240 (depends on wood species) 	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 85 to 90 (depends on wood species) • SD (Smoke Development) 305 to 365 (depends on wood species) 	Critical radiant flux (ASTM-E-648-94a): 0.46 to 0.47 watt/cm ² (depends on wood species)	R value: R 0.34 to 0.36 (depends on wood species)	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Lock) conform	
Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 85 to 110 Class C (depends on wood species) • SD (Smoke Development) 220 to 240 (depends on wood species) 	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 85 to 90 (depends on wood species) • SD (Smoke Development) 305 to 365 (depends on wood species) 								
Critical radiant flux (ASTM-E-648-94a): 0.46 to 0.47 watt/cm ² (depends on wood species)	R value: R 0.34 to 0.36 (depends on wood species)								
Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Lock) conform									
Provenance	Made in St-Georges, Qc, Canada.								
Use	Residential or light commercial								
Accessories	Round Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round, Round Stair Nosing for glued installation, Round Reducer for glued installation and underlayment.								
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 30% and 60%). • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications 								
Packaging	4-5/16"	5"	6-1/2"						
Content of a box	• 22 sq. ft.	• 32.60 sq. ft.	• 24.35 sq. ft.						
Size of a box	• 48" L x 9-1/2" W x 3-3/4" H	• 71" L x 10-3/4" W x 3-1/4" H	• 71" L x 7-1/2" W x 3-3/4" H						
Weight of a box	• 40 to 42 lbs	• 60 to 62 lbs	• 45 to 47 lbs						
Content of a pallet	• 40 boxes = 880 sq. ft.	• 36 boxes = 1,173.6 sq. ft.	• 48 boxes = 1,168.8 sq. ft.						
Size of a pallet	(4 boxes/W x 10 boxes/H)	(4 boxes/W x 9 boxes/H)	(6 boxes/W x 8 boxes/H)						
Relative species hardness	• 48" L x 38" W x 40" H	• 71" L x 42-3/4" W x 32-1/4" H	• 71-1/4" L x 44-1/2" W x 32-1/2" H						
NWFA Janka Test Hardness test (ASTM-D-143)	<ul style="list-style-type: none"> • Red Oak 1,290 lbs - average hardness • White Oak 1,360 lbs - 5% harder • Maple 1,450 lbs - 12% harder 								
Red Oak 1,290 lbs* - 100% *lbs = Applied force in pounds									

* Cashmere is a registered trademark used under license.

** 2G™ and 5G* are patented technologies invented by Välinge Innovation AB. The 2G™ and 5G* word marks and logos are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.

General Specifications



Characteristics	Mirage TruBalance		
Description	<ul style="list-style-type: none"> Structured prefinished hardwood flooring Incomparable tongue and groove fit for remarkable uniformity Micro-V bevel (on 4 sides) 		
Thickness	3/4" (Sawn hardwood layer 5/32", SPF Quarter sawn core layer 17/32" and wood backing board 1/16")		
Width	5"	6-1/2"	7-3/4"
Length ¹	Lengths from 20" (511 mm) to 82" (2,086 mm)		Lengths from 23" (590 mm) to 82" (2,086 mm)
Installation	Nailed, stapled, glued down or floated installation** (above, on or below grade)		
Subfloor	Wood, concrete or radiant heat system		
Species	5 species: Maple, Red Oak, White Oak, Hickory, Walnut		
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. ⚠️ Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 		
Color choice (refer to 2022 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart .		
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) Nanolinx® HD <ul style="list-style-type: none"> Cashmere® (18% gloss) Nanolinx® Commercial (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5		
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 90 Class C SD (Smoke Development) 80 Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSR (Flame Spread Rating) 107 SDC (Smoke Development Classification) 311 Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm ² (depends on wood species)		
Provenance	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (TruBalance) conform Made in St-Georges, Qc, Canada.		
Use	Residential, light commercial or commercial		
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round		
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (For the glued down and nailed/stapled installation relative humidity must be maintained within a range of 25% and 80%. For the floated installation relative humidity must be maintained between 30% and 60%). 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 		
Packaging	5"	6-1/2"	7-3/4"
Content of a box	• 22.70 sq. ft.	• 14.75 sq. ft.	• 17.60 sq. ft.
Size of a box	• 83" L x 10-1/2" W x 3-1/4" H	• 83" L x 7" W x 3-1/4" H	• 83" L x 8-3/8" W x 3-1/4" H
Weight of a box	• 42 to 45 lbs	• 27 to 31 lbs	• 32 to 36 lbs
Content of a pallet	• 48 boxes = 1,089.60 sq. ft. (4 boxes/W x 12 boxes/H)	• 72 boxes = 1,062 sq. ft. (6 boxes/W x 12 boxes/H)	• 60 boxes = 1,056 sq. ft. (5 boxes/W x 12 boxes/H)
Size of a pallet	• 83" L x 42" W x 42" H	• 83" L x 42" W x 42" H	• 83" L x 42" W x 42" H
Relative species hardness			
NWFA Janka Test Hardness test (ASTM-D-143)	<ul style="list-style-type: none"> Walnut 1,010 lbs - 22% softer Red Oak 1,290 lbs - average hardness White Oak 1,360 lbs - 5% harder 		
Red Oak 1,290 lbs* - 100%	<ul style="list-style-type: none"> Maple 1,450 lbs - 12% harder Hickory 1,820 lbs - 41% harder 		
*lbs = Applied force in pounds			

* Cashmere is a registered trademark used under license.

** For floated installation, please review the [TruBalance installation Guide](#) available on Mirage website in the [Guides and support section](#).

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.

Toll free : 1-800-463-1303



Characteristics	Mirage TruBalance										
	Herringbone										
Description	<ul style="list-style-type: none"> Structured prefinished hardwood flooring Micro-V bevel (on 4 sides) Incomparable tongue and groove fit for remarkable uniformity 										
Thickness	3/4" (Sawn hardwood layer 5/32", SPF Quarter sawn core layer 17/32" and wood backing board 1/16")										
Width	5" (127 mm)										
Length ¹	20" (508 mm)										
Installation	Glued down (above, on or below grade)										
Subfloor	Wood, concrete or radiant heat system										
Species	5 species: Maple, Red Oak, White Oak, Hickory, Walnut										
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. ⚠ Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 										
Color choice (refer to 2022 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart .										
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) Nanolinx® HD <ul style="list-style-type: none"> Cashmere* (18% gloss) Nanolinx® Commercial (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5										
Applicable standards	<table border="0"> <tr> <td> Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 90 Class C • SD (Smoke Development) 80 </td> <td> Surface Burning (ULC-S-102-2): • FSR (Flame Spread Rating) 107 • SDC (Smoke Development Classification) 311 </td> </tr> <tr> <td colspan="2"> Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm² (depends on wood species) </td> </tr> <tr> <td colspan="2"> Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (TruBalance) conform </td> </tr> </table>	Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 90 Class C • SD (Smoke Development) 80	Surface Burning (ULC-S-102-2): • FSR (Flame Spread Rating) 107 • SDC (Smoke Development Classification) 311	Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm ² (depends on wood species)		Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (TruBalance) conform					
Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 90 Class C • SD (Smoke Development) 80	Surface Burning (ULC-S-102-2): • FSR (Flame Spread Rating) 107 • SDC (Smoke Development Classification) 311										
Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm ² (depends on wood species)											
Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (TruBalance) conform											
Provenance	Made in St-Georges, Qc, Canada.										
Use	Residential, light commercial or commercial										
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round										
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must be maintained within a range of 25% and 80%). 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 										
Patterns	<table border="0"> <tr> <td> <ul style="list-style-type: none"> Herringbone Basket Double Herringbone </td> <td> <ul style="list-style-type: none"> Cube English pattern (bricks) Fence </td> </tr> </table>	<ul style="list-style-type: none"> Herringbone Basket Double Herringbone 	<ul style="list-style-type: none"> Cube English pattern (bricks) Fence 								
<ul style="list-style-type: none"> Herringbone Basket Double Herringbone 	<ul style="list-style-type: none"> Cube English pattern (bricks) Fence 										
Packaging	5"										
Content of a box	16.67 sq. ft.										
Size of a box	62-1/4" L x 10-3/4" W x 3-1/4" H										
Weight of a box	28 to 32 lbs										
Content of a pallet	48 boxes = 800.16 sq. ft. (4 boxes/W x 12 boxes/H)										
Size of a pallet	61-1/4" L x 42-1/2" W x 42-1/2" H										
Relative species hardness	<table border="0"> <tr> <td>• Walnut</td> <td>1,010 lbs - 22% softer</td> </tr> <tr> <td>• Red Oak</td> <td>1,290 lbs - average hardness</td> </tr> <tr> <td>• White Oak</td> <td>1,360 lbs - 5% harder</td> </tr> <tr> <td>• Maple</td> <td>1,450 lbs - 12% harder</td> </tr> <tr> <td>• Hickory</td> <td>1,820 lbs - 41% harder</td> </tr> </table>	• Walnut	1,010 lbs - 22% softer	• Red Oak	1,290 lbs - average hardness	• White Oak	1,360 lbs - 5% harder	• Maple	1,450 lbs - 12% harder	• Hickory	1,820 lbs - 41% harder
• Walnut	1,010 lbs - 22% softer										
• Red Oak	1,290 lbs - average hardness										
• White Oak	1,360 lbs - 5% harder										
• Maple	1,450 lbs - 12% harder										
• Hickory	1,820 lbs - 41% harder										
NWFA Janka Test Hardness test (ASTM-D-143)											
Red Oak 1,290 lbs* - 100%											
*lbs = Applied force in pounds											

* Cashmere is a registered trademark used under license.

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.