



Characteristics	Mirage Classic		
	Alive Collection		
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) • Brushed 		
Thickness	3/4" (19 mm)		
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))		
Width	2-1/4" (57 mm)	2-1/2" (64 mm) and 3-1/4" (83 mm)	4-1/4" (108 mm)
Species	1 species: Red Oak		
Grade	• Exclusive (As found in nature. A complete species color and character range)		
Color choice (refer to 2017 Mirage Collections)	7 colors : Oakland, Stanford, Farnham, Eastman, Knowlton, Isla, Sepia Some products may not be available. Ask your Mirage representative or consult the product chart.		
Finish	<ul style="list-style-type: none"> • Nanolinx™ HD: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • Cashmere®* (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55		
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 • Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species) R value: R 0.6 to 0.8 (depends on wood species)		
Installation	Nailed or stapled down (above and on grade)		
Subfloor	Wood		
Provenance	Made in St-Georges, Qc, Canada.		
Uses	Residential or light commercial		
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round		
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications 		
Packaging	2-1/4" (57 mm)	2-1/2" (64 mm) and 3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft ² (1,858 m ²)	• 20 ft ² (1,858 m ²)	• 18 ft ² (1,672 m ²)
Size of a box	• 86" L x 9-1/2" W x 3-1/4" H	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft ²	• 48 boxes = 960 ft ²	• 48 boxes = 864 ft ²
Size of a pallet	(4 boxes/W x 12 boxes/H) • 86" L x 38" W x 43" H	(4 boxes/W x 12 boxes/H) • 79" L x 42" W x 43" H	(4 boxes/W x 12 boxes/H) • 85-1/2" L x 38" W x 43" H
Relative species hardness			
NWFA Janka Test	• Red Oak	1,290 lbs - average hardness	
Hardness test (ASTM-D-143)			
Red Oak 1290 lbs* - 100%			
*lbs = Applied force in pounds			

* Cashmere is a registered trademark used under license.