



Characteristics	Mirage Classic	
Description	<ul style="list-style-type: none"> • For Admiration, Natural, Flair, Sweet Memories, Imagine and Escape Collections • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) 	
Thickness	3/4"	
Width	3-1/4"	4-1/4"
Length	Random lengths from 10" to 76"	
Installation	Nailed or stapled down (above and on grade)	
Subfloor	Wood	
Species	3 species: Maple, Red Oak, White Oak	
Grade	<ul style="list-style-type: none"> • Select & Better: Selection of more uniform wood grain with slight variations in natural shading • Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. • Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 	
Color choice (refer to 2021 Mirage Collections)	52 colors: Auburn, Black Jelly Bean, Bubble Bath, Canyon, Cape Cod, Carmel, Carousel, Charcoal, Château, Coffee, Cold Springs, Destin, Driftwood, Gelato, Gingerbread, Golden, Greystone, Graphite, Havana, Hopscotch, Hula Hoop, Isla, Jump Rope, Laguna, Lunar Eclipse, Mystic Island, Natural, Nevada, New Haven, Nordic, Nougat, Paddle Ball, Papyrus, Peppermint, Platinum, Praline, Providence, Rio, Rock Cliff, Rocking Horse, Roller Coaster, Sailing Stone, Sand Castle, Sandstone, Savanna, Sierra, Snowdrift, Stardust, Stillwater, Treasure, Tree House, White Mist. Some products may not be available. Ask your Mirage representative or consult the product chart.	
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> • DuraMatt® (5% gloss) • Nanolinx® HD Semi-gloss (50% gloss) or Cashmere®* (18% gloss) • Nanolinx® Commercial (18% gloss): Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5	
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species) Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Classic) conform	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) R value: R 0.6 to 0.8 (depends on wood species)
Provenance	Made in St-Georges, Qc, Canada.	
Use	Residential, light commercial or commercial (Nanolinx® Commercial)	
Accessories	Round Stair nosing, Square Stair nosing, Round Reducer, Multifunction reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 35% and 55%). 	<ul style="list-style-type: none"> • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications • 5-year finish warranty for commercial applications with Nanolinx® Commercial
Packaging	3-1/4"	4-1/4"
Content of a box	• 20 sq. ft.	• 18 sq. ft.
Size of a box	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 sq. ft. (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 sq. ft. (4 boxes/W x 12 boxes/H)
Size of a pallet	• 79" L x 42" W x 42" H	• 85-1/2" L x 37" W x 42" H
Relative species hardness		
NWFA Janka Test	• Red Oak 1,290 lbs - average hardness	
Hardness test (ASTM-D-143)	• White Oak 1,360 lbs - 5% harder	
	• Maple 1,450 lbs - 12% harder	
Red Oak 1290 lbs* - 100%		
*lbs = Applied force in pounds		

* Cashmere is a registered trademark used under license.



Characteristics	Mirage Engineered			
Description	<ul style="list-style-type: none"> For Admiration, Natural, Flair, Sweet Memories, Imagine, Escape and DreamVille Collections Engineered prefinished hardwood flooring with tongues and grooves Micro-V bevel (on 4 sides) 			
Thickness	1/2" (Sawn hardwood layer 5/32", 7-ply plywood base 11/32")			
Width	5"-Escape & Dreamville	5"	6-1/2"	7"
Length	Lengths from 17" to 69"		Lengths from 20" to 82"	
Installation	Nailed, stapled or glued (above, on or below grade)			
Subfloor	Wood, concrete or radiant heat system			
Species	4 species: Maple, Red Oak, White Oak, Walnut			
Grade	<ul style="list-style-type: none"> Select & Better: Selection of more uniform wood grain with slight variations in natural shading Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 			
Color choice (refer to 2021 Mirage Collections)	57 colors: Aspen, Auburn, Black Jelly Bean, Bubble Bath, Canyon, Cape Cod, Carmel, Carousel, Charcoal, Château, Coffee, Cold Springs, Destin, Driftwood, Florence, Gelato, Gingerbread, Golden, Greystone, Graphite, Havana, Hermosa, Hopscotch, Hudson, Hula Hoop, Isla, Key Largo, Laguna, Lunar Eclipse, Maui, Morro Bay, Mystic Island, Natural, Nevada, New Haven, Nordic, North Hatley, Nougat, Papyrus, Park City, Peppermint, Platinum, Praline, Providence, Rio, Rock Cliff, Roller Coaster, Sand Castle, Sandstone, Savanna, Sierra, Snowdrift, Stillwater, Treasure, Tree House, Waterloo, White Mist. Some products may not be available. Ask your Mirage representative or consult the product chart.			
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) DuraMatt® X (10% gloss) Nanolinx® HD Semi-gloss (50% gloss) or Cashmere* (18% gloss) Nanolinx® Commercial (18% gloss): Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5			
Applicable standards	5" - Escape-Dreamville - 5" - 6-1/2" - 7" Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) SD (Smoke Development) < 400 (depends on wood species) Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSV (Flame Spread Value) 80 (depends on wood species) SD (Smoke Development) < 350 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm ² (depends on wood species) R value: R 0.44 to 0.48 (depends on wood species) Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Engineered) conform			
Provenance	Made in St-Georges, Qc, Canada.			
Use	Residential, light commercial or commercial (Nanolinx® Commercial)			
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round			
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty Relative humidity must always be maintained within a range of 25% and 70%. 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 			
Packaging	5"-Escape & Dreamville	5"	6-1/2"	7"
Content of a box	• 28.50 sq. ft.	• 34.10 sq. ft.	• 22.15 sq. ft.	• 23.8 sq. ft.
Size of a box	• 70-3/4" L x 10-3/4" W x 3-1/4" H	• 83" L x 10-1/2" W x 3-1/4" H	• 83" L x 7" W x 3-1/4" H	• 83-1/2" L x 7-1/2" W x 3-1/4" H
Weight of a box	• 53 lbs	• 65 to 70 lbs	• 42 to 45 lbs	• 44 to 47 lbs
Content of a pallet	• 48 boxes = 1,368 sq. ft.	• 32 boxes = 1,091.2 sq. ft.	• 48 boxes = 1,063.2 sq. ft.	• 50 boxes = 1,190 sq. ft.
Size of a pallet	(4 boxes/W x 12 boxes/H) • 71" L x 43" W x 43" H	(4 boxes/W x 8 boxes/H) • 83" L x 42" W x 30" H	(6 boxes/W x 8 boxes/H) • 83" L x 42" W x 30" H	(5 boxes/W x 10 boxes/H) • 83" L x 37-1/2" W x 36" H
Relative species hardness	<ul style="list-style-type: none"> Walnut 1,010 lbs - 22% softer Red Oak 1,290 lbs - average hardness White Oak 1,360 lbs - 5% harder Maple 1,450 lbs - 12% harder Red Oak 1,290 lbs* - 100% *lbs = Applied force in pounds			

* Cashmere is a registered trademark used under license.



Characteristics	Mirage Engineered								
	Herringbone								
Description	<ul style="list-style-type: none"> Engineered prefinished hardwood flooring with tongue and groove edges, and grooves at both ends Micro-V bevel (on 4 sides) 								
Thickness	1/2" (Sawn hardwood layer 5/32", 7-ply plywood base 11/32")								
Width	5"								
Length	20"								
Installation	Glued down (above, on or below grade)								
Subfloor	Wood, concrete or radiant heat system								
Species	4 species: Maple, Red Oak, White Oak, Walnut								
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. ⚠ Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 								
Color choice (refer to 2021 Mirage Collections)	27 colors: Auburn, Bubble Bath, Canyon, Cape Cod, Charcoal, Coffee, Gelato, Golden, Greystone, Graphite, Havana, Hopscotch, Hudson, Hula Hoop, Lunar Eclipse, Natural, Nevada, Nordic, Peppermint, Platinum, Rio, Roller Coaster, Sand Castle, Savanna, Sierra, Snowdrift, White Mist. Some products may not be available. Ask your Mirage representative or consult the product chart.								
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) Nanolinx® HD Semi-gloss (50% gloss) or Cashmere®* (18% gloss) Nanolinx® Commercial (18% gloss): Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5								
Applicable standards	<table border="0"> <tr> <td> Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) • SD (Smoke Development) < 400 (depends on wood species) </td> <td> Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 80 (depends on wood species) • SD (Smoke Development) < 350 (depends on wood species) </td> </tr> <tr> <td> Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm² (depends on wood species) </td> <td> R value: R 0.44 to 0.48 (depends on wood species) </td> </tr> <tr> <td colspan="2"> Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Engineered) conform </td> </tr> </table>	Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) • SD (Smoke Development) < 400 (depends on wood species)	Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 80 (depends on wood species) • SD (Smoke Development) < 350 (depends on wood species)	Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm ² (depends on wood species)	R value: R 0.44 to 0.48 (depends on wood species)	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Engineered) conform			
Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) • SD (Smoke Development) < 400 (depends on wood species)	Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 80 (depends on wood species) • SD (Smoke Development) < 350 (depends on wood species)								
Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm ² (depends on wood species)	R value: R 0.44 to 0.48 (depends on wood species)								
Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Engineered) conform									
Provenance	Made in St-Georges, Qc, Canada.								
Use	Residential, light commercial or commercial (Nanolinx® Commercial)								
Accessories	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round								
Warranty	<table border="0"> <tr> <td> • Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 25% and 70%). </td> <td> • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications • 5-year finish warranty for commercial applications with Nanolinx® Commercial </td> </tr> </table>	• Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 25% and 70%).	• 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications • 5-year finish warranty for commercial applications with Nanolinx® Commercial						
• Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 25% and 70%).	• 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications • 5-year finish warranty for commercial applications with Nanolinx® Commercial								
Patterns	<table border="0"> <tr> <td> • Herringbone • Basket • Double Herringbone </td> <td> • Cube • English pattern (bricks) • Fence </td> </tr> </table>	• Herringbone • Basket • Double Herringbone	• Cube • English pattern (bricks) • Fence						
• Herringbone • Basket • Double Herringbone	• Cube • English pattern (bricks) • Fence								
Packaging	Length: 20"								
Content of a box	• 25 sq. ft.								
Size of a box	• 61" L x 10-1/2" W x 3-1/4" H								
Weight of a box	• 46 to 51 lbs								
Content of a pallet	• 40 boxes = 1,000 sq. ft. (4 boxes/W x 10 boxes/H)								
Size of a pallet	• 61" L x 42" W x 37" H								
Relative species hardness									
NWFA Janka Test	<table border="0"> <tr> <td>• Walnut</td> <td>1,010 lbs - 22% softer</td> </tr> <tr> <td>• Red Oak</td> <td>1,290 lbs - average hardness</td> </tr> <tr> <td>• White Oak</td> <td>1,360 lbs - 5% harder</td> </tr> <tr> <td>• Maple</td> <td>1,450 lbs - 12% harder</td> </tr> </table>	• Walnut	1,010 lbs - 22% softer	• Red Oak	1,290 lbs - average hardness	• White Oak	1,360 lbs - 5% harder	• Maple	1,450 lbs - 12% harder
• Walnut	1,010 lbs - 22% softer								
• Red Oak	1,290 lbs - average hardness								
• White Oak	1,360 lbs - 5% harder								
• Maple	1,450 lbs - 12% harder								
Hardness test (ASTM-D-143)									
Red Oak 1,290 lbs* - 100%									
*lbs = Applied force in pounds									

* Cashmere is a registered trademark used under license.



Characteristics	Mirage Lock	
Description	<ul style="list-style-type: none"> • For Admiration, Natural, Flair, Sweet Memories, Imagine and Escape Collections • Lock prefinished hardwood flooring • Rightloc™ locking system • Incomparable tongue and groove fit for remarkable uniformity • Micro-V bevel (on 4 sides) 	
Thickness	7/16" (Sawn hardwood layer 1/16", HDF Core 9/32" and wood backing board)	
Width	4-5/16"	5"
Length	Lengths from 14" to 46"	Lengths from 17" to 69"
Installation	Floated over a recommended membrane or glued down (above, on or below grade)	
Subfloor	Wood, concrete or radiant heat system	
Species	3 species: Maple, Red Oak, White Oak	
Grade	<ul style="list-style-type: none"> • Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. • ▲ Character floors: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 	
Color choice (refer to 2021 Mirage Collections)	51 colors: Auburn, Black Jelly Bean, Bubble Bath, Canyon, Cape Cod, Carmel, Carousel, Charcoal, Château, Coffee, Cold Springs, Destin, Driftwood, Gelato, Gingerbread, Golden, Graphite, Grey Drizzle, Greystone, Havana, Hopscotch, Hula Hoop, Jump Rope, Laguna, Lunar Eclipse, Mystic Island, Natural, Nevada, New Haven, Nordic, Nougat, Paddle Ball, Papyrus, Park City, Peppermint, Platinum, Praline, Providence, Rich Oak, Rio, Rock Cliff, Rocking Horse, Roller Coaster, Sailing Stone, Sandstone, Sand Castle, Savanna, Sierra, Snowdrift, Stardust, Stillwater, Treasure, Tree House, White Mist. Some products may not be available. Ask your Mirage representative or consult the product chart.	
Finish	<ul style="list-style-type: none"> • DuraMatt®: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • Nanolinx® HD: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> • Semi-gloss (50% gloss) or Cashmere®* (18% gloss) 	
	UV Protection: All products	
	Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5	
Applicable standards	Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 85 to 110 Class C (depends on wood species) • SD (Smoke Development) 220 to 240 (depends on wood species)	Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 85 to 90 (depends on wood species) • SD (Smoke Development) 305 to 365 (depends on wood species)
	Critical radiant flux (ASTM-E-648-94a): 0.46 to 0.47 watt/cm ² (depends on wood species)	R value: R 0.34 to 0.36 (depends on wood species)
	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Lock) conform	
Provenance	Made in St-Georges, Qc, Canada.	
Use	Residential or light commercial	
Accessory	Round Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round and membrane	
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 30% and 60%). 	<ul style="list-style-type: none"> • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications
Packaging	4-5/16"	5"
Content of a box	• 22 sq. ft.	• 32.60 sq. ft.
Size of a box	• 48" L x 9-1/2" W x 3-3/4" H	• 71" L x 10-3/4" W x 3-1/4" H
Weight of a box	• 42 lbs	• 62 lbs
Content of a pallet	• 40 boxes = 880 sq. ft. (4 boxes/W x 10 boxes/H)	• 36 boxes = 1,174 sq. ft. (4 boxes/W x 9 boxes/H)
Size of a pallet	• 48" L x 38" W x 40" H	• 71" L x 43" W x 32" H
Relative species hardness		
NWFA Janka Test	• Red Oak	1,290 lbs - average hardness
Hardness test (ASTM-D-143)	• White Oak	1,360 lbs - 5% harder
	• Maple	1,450 lbs - 12% harder
Red Oak 1,290 lbs* - 100%		
*lbs = Applied force in pounds		



Characteristics	Mirage TruBalance		
Description	<ul style="list-style-type: none"> For Admiration, Natural, Flair, Sweet Memories and Imagine Collections Structured prefinished hardwood flooring Incomparable tongue and groove fit for remarkable uniformity Micro-V bevel (on 4 sides) 		
Thickness	3/4" (Sawn hardwood layer 5/32", SPF Quarter sawn core layer 17/32" and wood backing board 1/16")		
Width	5"	6-1/2"	7-3/4"
Length	Lengths from 20" to 82"		Lengths from 23" to 82"
Installation	Nailed, stapled, glued down or floated installation** (above, on or below grade)		
Subfloor	Wood, concrete or radiant heat system		
Species	5 species: Maple, Red Oak, White Oak, Hickory, Walnut		
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 		
Color choice (refer to 2021 Mirage Collections)	50 colors: Auburn, Black Jelly Bean, Bubble Bath, Canyon, Cape Cod, Carousel, Charcoal, Château, Clay Marbles, Coffee, Desert Rose, Driftwood, Gelato, Gingerbread, Golden, Graphite, Greystone, Havana, Hopscotch, Hudson, Hula Hoop, Isla, Jump Rope, Lunar Eclipse, Natural, Nevada, Nordic, North Hatley, Nougat, Paddle Ball, Papyrus, Peppermint, Platinum, Praline, Rio, Rock Cliff, Rocking Horse, Roller Coaster, Sailing Stone, Sandstone, Sand Castle, Sandy Reef, Savanna, Sierra, Snowdrift, Stardust, Treasure, Tree House, Waterloo, White Mist. Some products may not be available. Ask your Mirage representative or consult the product chart.		
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) Nanolinx® HD Cashmere®* (18% gloss) Nanolinx® Commercial (18% gloss): Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5		
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 90 Class C SD (Smoke Development) 80 Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSR (Flame Spread Rating) 107 SDC (Smoke Development Classification) 311 Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm² (depends on wood species)		
Provenance	Made in St-Georges, Qc, Canada.		
Use	Residential, light commercial or commercial		
Accessories	Round Stair nosing, Square Stair nosing, Round Reducer, Multifunction Reducer, Threshold, "T" molding, Quarter round		
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (For the glued down and nailed/stapled installation relative humidity must be maintained within a range of 25% and 80%. For the floated installation relative humidity must be maintained between 30% and 60%). 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 		
Packaging	5"	6-1/2"	7-3/4"
Content of a box	• 22.70 sq. ft.	• 14.75 sq. ft.	• 17.60 sq. ft.
Size of a box	• 83" L x 10-3/4" W x 3-1/4" H	• 83" L x 7" W x 3-1/4" H	• 83" L x 8-3/8" W x 3-1/4" H
Weight of a box	• 42 to 45 lbs	• 27 to 31 lbs	• 32 to 36 lbs
Content of a pallet	• 48 boxes = 1,089.60 sq. ft. (4 boxes/W x 12 boxes/H)	• 48 boxes = 708 sq. ft. (4 boxes/W x 12 boxes/H)	• 60 boxes = 1,056 sq. ft. (5 boxes/W x 12 boxes/H)
Size of a pallet	• 83" L x 43" W x 42" H	• 83" L x 42" W x 42" H	• 83" L x 41-1/4" W x 36" H
Relative species hardness			
NWFA Janka Test	<ul style="list-style-type: none"> Walnut 1,010 lbs - 22% softer Red Oak 1,290 lbs - average harder White Oak 1,360 lbs - 5% harder Maple 1,450 lbs - 12% harder Hickory 1,820 lbs - 41% harder 		
Hardness test (ASTM-D-143)			
Red Oak 1,290 lbs* - 100% *lbs = Applied force in pounds			

* Cashmere is a registered trademark used under license.

** For floated installation, please review the TruBalance installation Guide available on Mirage website in the Guides and support section.



Characteristics	Mirage TruBalance
	Herringbone
Description	<ul style="list-style-type: none"> For Natural, Flair and Sweet Memories Collections Structured prefinished hardwood flooring Micro-V bevel (on 4 sides) Incomparable tongue and groove fit for remarkable uniformity
Thickness	3/4" (Sawn hardwood layer 5/32", SPF Quarter sawn core layer 17/32" and wood backing board 1/16")
Width	5"
Length	30"
Installation	Glued down (above, on or below grade)
Subfloor	Wood, concrete or radiant heat system
Species	4 species: Maple, Red Oak, White Oak, Hickory
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. ⚠ Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.
Color choice (refer to 2021 Mirage Collections)	16 colors: Bubble Bath, Desert Rose, Gelato, Hopscotch, Hula Hoop, Lunar Eclipse, Natural, Paddle Ball, Peppermint, Roller Coaster, Sailing Stone, Sand Castle, Sandy Reef, Snowdrift, Stardust, White Mist. Some products may not be available. Ask your Mirage representative or consult the product chart.
Finish	<ul style="list-style-type: none"> DuraMatt® (5% gloss): Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 90 Class C SD (Smoke Development) 80 Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSR (Flame Spread Rating) 107 SDC (Smoke Development Classification) 311 Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm ² (depends on wood species)
Provenance	Made in St-Georges, Qc, Canada.
Use	Residential, light commercial or commercial
Accessories	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must be maintained within a range of 25% and 80%). 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications
Patterns	<ul style="list-style-type: none"> Herringbone Basket Double Herringbone Cube English pattern (bricks) Fence
Packaging	Length: 30"
Content of a box	16.67 sq. ft.
Size of a box	61-1/4" L x 10-3/4" W x 3-1/4" H
Weight of a box	28 to 32 lbs
Content of a pallet	40 boxes = 666.8 sq. ft. (4 boxes/W x 10 boxes/H)
Size of a pallet	61-1/4" L x 42-1/2" W x 36" H
Relative species hardness	
NWFA Janka Test	<ul style="list-style-type: none"> Walnut 1,010 lbs - 22% softer Red Oak 1,290 lbs - average harder White Oak 1,360 lbs - 5% harder Maple 1,450 lbs - 12% harder Hickory 1,820 lbs - 41% harder
Hardness test (ASTM-D-143)	
Red Oak 1,290 lbs* - 100%	
*lbs = Applied force in pounds	

* Cashmere is a registered trademark used under license.