





Characteristics	Mirage Classic	
	Sweet Memories Collection	
Description	<ul style="list-style-type: none"> Solid prefinished hardwood flooring with tongues and grooves Micro-V bevel (on 4 sides) An exclusive variable staining process 	
Thickness	3/4" (19 mm)	
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))	
Width	3-1/4" (83 mm)	4-1/4" (108 mm)
Species	1 species: Maple Character	2 species: Maple Character, Yellow Birch Character
Grade	<ul style="list-style-type: none"> Character-looking floors: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 	
Color choice (refer to 2017 Mirage Collections)	6 colors: Gelato, Peppermint, Nougat, Praline, Gingerbread, Black Jelly Bean	
Finish	<ul style="list-style-type: none"> Nanolinx HD™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. Cashmere®* (18% gloss) 	
	UV Protection: All products	Formaldehyde: Free
	Water and solvent: No trace	
	Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55	
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species) SD (Smoke Development) 75 to 400 (depends on wood species) 	
	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSV (Flame Spread Value) 100 to 150 (depends on wood species) SD (Smoke Development) 200 to 300 (depends on wood species) 	
	Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species)	
	R value: R 0.6 to 0.8 (depends on wood species)	
	Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform	
Installation	Nailed or stapled down (above and on grade)	
Subfloor	Wood	
Provenance	Made in St-Georges, Qc, Canada.	
Use	Residential or light commercial	
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty 35-year finish warranty for residential applications 	<ul style="list-style-type: none"> 3-year finish warranty for light commercial applications
Packaging	3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft ² (1,858 m ²)	• 18 ft ² (1,672 m ²)
Size of a box	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft ² (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 ft ² (4 boxes/W x 12 boxes/H)
Size of a pallet	• 79" L x 42" W x 43" H	• 85-1/2" L x 38" W x 43" H
Relative species hardness		
NWFA Janka Test	• Yellow Birch	1,260 lbs - 2% softer
Hardness test (ASTM-D-143)	• Maple	1,450 lbs - 12% harder
Red Oak 1290 lbs* - 100%		
*lbs = Applied force in pounds		

* Cashmere is a registered trademark used under license.



Characteristics	Mirage Classic	
	Sweet Memories Collection 	
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) • Antique look, Brushed 	
Thickness	3/4" (19 mm)	
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))	
Width	3-1/4" (83 mm)	4-1/4" (108 mm)
Species	1 species: Red Oak Character	
Grade	<ul style="list-style-type: none"> •  Character-looking floors: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 	
Color choice (refer to 2017 Mirage Collections)	5 colors: Carousel, Château, Treasure, Hopscotch, Tree House	
Finish	<ul style="list-style-type: none"> • Nanolinx HD™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • Cashmere®* (18% gloss) 	
	UV Protection: All products	Formaldehyde: Free
	Water and solvent: No trace	
	Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55	
Applicable standards	<p>Surface Burning (ASTM-E-84):</p> <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 • Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) <p>Critical radiant flux (ASTM-E-648-94a):</p> <p>0.25 to 0.40 watt/cm² (depends on wood species)</p> <p>Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform</p>	
	<p>Surface Burning (ULC-S-102-2):</p> <ul style="list-style-type: none"> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) <p>R value: R 0.6 to 0.8 (depends on wood species)</p>	
Installation	Nailed or stapled down (above and on grade)	
Subfloor	Wood	
Provenance	Made in St-Georges, Qc, Canada.	
Use	Residential or light commercial	
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty • 35-year finish warranty for residential applications 	<ul style="list-style-type: none"> • 3-year finish warranty for light commercial applications
Packaging	3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft ² (1.858 m ²)	• 18 ft ² (1.672 m ²)
Size of a box	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft ²	• 48 boxes = 864 ft ²
	(4 boxes/W x 12 boxes/H)	(4 boxes/W x 12 boxes/H)
Size of a pallet	• 79" L x 42" W x 43" H	• 85-1/2" L x 38" W x 43" H
Relative species hardness		
NWFA Janka Test	• Red Oak	1,290 lbs - average hardness
Hardness test (ASTM-D-143)		
Red Oak 1290 lbs* - 100%		
*lbs = Applied force in pounds		

* Cashmere is a registered trademark used under license.