



Characteristics	Mirage Classic			
Description	<ul style="list-style-type: none"> • For Admiration, Alive, Natural, Flair, Sweet Memories and Imagine collections • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) 			
Thickness	3/4" (19 mm)			
Length	Random lengths (from 10" (250 mm) to 76" (1,930 mm))			
Width	2-1/4" (57 mm)	2-1/2" (64 mm)	3-1/4" (83 mm)	4-1/4" (108 mm)
Species	4 species: Maple, Red Oak, White Oak and Yellow Birch.			
Grade	<ul style="list-style-type: none"> • Select & Better: Selection of more uniform wood grain with slight variations in natural shading • Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. • Character-looking floors: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 			
Color choice (refer to 2018 Mirage Collections)	<p>60 colors: Nordic, Greystone, Charcoal, Graphite, Isla, Cape Cod, Rio, Savanna, Rich Oak, Havana, Java, Coffee, Sierra, Golden, Nevada, Auburn, Canyon, Umbria, Vienna, Platinum, Hudson, North Hatley, Windsor, Bolton, Waterloo, Oakland, Farnham, Stanford, Eastman, Knowlton, Natural, White Mist, Snowdrift, Sand Dune, Grey Drizzle, Dark Leaf, Lunar Eclipse, Nightfall, Bubble Bath, Hula Hoop, Carousel, Sand Castle, Château, Roller Coaster, Gelato, Treasure, Peppermint, Hopscotch, Nougat, Tree House, Praline, Gingerbread, Black Jelly Bean, Driftwood, Rock Cliff, Barn Wood, Papyrus, Seashell, Sandstone, Fossil.</p> <p>Some products may not be available. Ask your Mirage representative or consult the product chart.</p>			
Finish	<ul style="list-style-type: none"> • Nanolinx™ HD: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> • Semi-gloss (50% gloss) or Cashmere®* (18% gloss) • Nanolinx™ Commercial: Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • DuraMatt™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <p>UV Protection: All products</p> <p>Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55</p>			
Applicable standards	<p>Surface Burning (ASTM-E-84): FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species)</p> <p>Surface Burning (ULC-S-102-2): FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species)</p> <p>Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm² (depends on wood species) R value: R 0.6 to 0.8 (depends on wood species)</p> <p>Formaldehyde and VOC emissions (CDPH 1.1, 2010): Target product group (Classic) conform</p>			
Installation	Nailed or stapled down (above and on grade)			
Subfloor	Wood			
Provenance	Made in St-Georges, Qc, Canada.			
Use	Residential or light commercial			
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round			
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications • 5-year finish warranty for commercial applications with Nanolinx™ Commercial 			
Packaging	2-1/4" (57 mm)	2-1/2" (64 mm)	3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft ² (1 858 m ²)	• 20 ft ² (1 858 m ²)	• 20 ft ² (1 858 m ²)	• 18 ft ² (1 672 m ²)
Size of a box	• 86" L x 9-1/2" W x 3-1/4" H	• 79" L x 10-1/2" W x 3-1/4" H	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 49 to 60 lbs	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft ² (4 boxes/W x 12 boxes/H)	• 48 boxes = 960 ft ² (4 boxes/W x 12 boxes/H)	• 48 boxes = 960 ft ² (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 ft ² (4 boxes/W x 12 boxes/H)
Size of a pallet	• 86" L x 38" W x 42" H	• 79" L x 42" W x 42" H	• 79" L x 42" W x 42" H	• 85-1/2" L x 37" W x 42" H
Relative species hardness				
NWFA Janka Test	• Yellow Birch	1,260 lbs - 2% softer		
Hardness test (ASTM-D-143)	• Red Oak	1,290 lbs - average hardness		
	• White Oak	1,360 lbs - 12% harder		
Red Oak 1290 lbs* - 100%	• Maple	1,450 lbs - 12% harder		
*lbs = Applied force in pounds				

* Cashmere is a registered trademark used under license.