



Characteristics	Mirage TruBalance Lite	
	Herringbone	
Description	<ul style="list-style-type: none"> Structured prefinished hardwood flooring Micro-V bevel (on 4 sides) Incomparable tongue and groove fit for remarkable uniformity 	
Thickness	9/16" (14 mm) (Real Hardwood Top Lamella 3 mm, Locally Sourced SPF Quarter Sawn* Core layer 9 mm and Wood Backing Veneer 2 mm)	
Width	5" (127 mm)	
Length	Fixed 20" (508 mm)	
Installation	Glued down (above, on or below grade)	
Subfloor	Wood, concrete or radiant heat system	
Species	4 species: Red Oak, Oak, White Oak, Maple	
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a limited range of color variation. Character: These floors are appreciated for their pronounced color variations. They feature open and closed knots, mineral streaks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 	
Color choice (Refer to 2025 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart	
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) DuraMatt® X (10% gloss) DurAlive™ (12% gloss) Cashmere*** uses Nanolinx® technology (18% gloss) Nanolinx Commercial (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5	
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) Coming soon SD (Smoke Development) Coming soon Critical radiant flux (ASTM-E-648-94a): Coming soon	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSR (Flame Spread Rating) Coming soon SDC (Smoke Development Classification) Coming soon R value: R 0.86 to 0.89 (depends on wood species)
Provenance	Made in St-Georges, Qc, Canada.	
Use	Residential, light commercial or commercial	
Accessory	Matchable Square Stair Nosing, Round Reducer, Threshold, "T" Molding, Quarter Round, Wood Flush Mount Vent Acoustitech underlayments are recommended by Mirage. To know more about the minimum criteria needed regarding the recommended waterproof acoustic underlayment, please refer to the Technical Newsletter #20 in the Guides and Support section at miragefloors.com .	
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (For the glued down and nailed/stapled installation relative humidity must be maintained within a range of 25% and 70%. For the floated installation relative humidity must be maintained between 30% and 60%) 	<ul style="list-style-type: none"> 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications
Patterns	<ul style="list-style-type: none"> Herringbone Double Herringbone Basket 	<ul style="list-style-type: none"> Cube English pattern (bricks) Fence
Packaging	5" (127 mm)	
Content of a box	25 sq. ft. (2,32 m ²)	
Size of a box	71" L x 10-1/2" W x 3-1/2" H	
Weight of a box	37 to 39 lb	
Content of a pallet	44 boxes = 1,100 sq. ft. (4 boxes/W x 11 boxes/H)	
Size of a pallet	71" L x 42-1/2" W x 42-1/4" H	
Relative species hardness		
NWFA Janka Test	Red Oak	1,290 lbs - average hardness
Hardness test (ASTM-D-143)	Oak	1,290 lbs - average hardness
	White Oak	1,360 lbs - 5% harder
Red Oak 1,290 lbs* - 100%	Maple	1,450 lbs - 12% harder
*lbs = Applied force in pounds		

* Predominantly Quarter Sawn.

** Cashmere is a trademark used under licence.

1. Values in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks value.