

Quick and easy installation

1. Inspect and repair subfloor. Make sure it meets the standards described in Mirage Lock product installation guide.
2. Make sure subfloor is free of dust and debris.
3. Install one roll of the underlayment in the perpendicular direction you plan to install the flooring planks.
4. Leave the edges of each strip raised [2"]. Install the next roll of underlayment without overlapping the first one [Figure 1].
5. Remove the protection on the adhesive strip and seal the underlayment joints with aluminum strip.
6. Make sure you have a continuous sealed joint to avoid any moisture infiltration [Figure 2].
7. Use recommended sealing tape and seal the underlayment strips on ends, in corner joints and around any break through or opening made in the underlayment [Figure 2].




Figure 1




Figure 2



Mirage recommends and distributes **Ulti-Mat** for use under Mirage Lock floors

Technical Specifications

Description	Ulti-Mat Underlayment	
Core Material	Polyolefin	
Width	48"	
Length	25'	
Thickness	0.080" [2 mm]	
Packaging	100 sq. ft. per roll [12 rolls per box]	
Color	Gold yellow	
Film	Polyethylene [aluminum]	
Installation	Under Lock floors and other glueless floors	
Subfloor	Wood or Concrete	
Acoustic	8" concrete slab	Other
Impact Insulation Class [IIC]	63	74
Sound Transmission Class [STC]	56	73
Sealing tape recommended	Tucktape/LTD #20502 or equivalent	

Warranty - 25 years

The manufacturer warrants Ulti-Mat acoustic and moisture-resistant underlayment to be free from manufacturing defects in materials and workmanship for a period of 25 years from the date the product was originally purchased [the Limited Warranty Period]. In addition, the manufacturer also warrants its Ulti-Mat underlayment against material breakdown, deterioration, or disintegration for a period of 25 years for the original resident or property owner.

For more information: 1 800 440-6008

www.miragelock.com



Litho Canada | 1109_17112E1.2



Ulti-Mat is the ideal underlayment choice for use under Mirage Lock floors. The high performance underlayment ensures peace of mind.

Many advantages

- Higher acoustic insulation;
This underlayment is the best choice for condominium floors because it reduces sound transmission and impact insulation for quiet living.
- True vapor barrier system
- Perfect density for increased comfort and stability
- Compact and light for easy handling
- No glue or nails
- 25 year warranty