



Characteristics	Mirage TruBalance										
	Herringbone										
Description	<ul style="list-style-type: none"> For Natural, Flair and Sweet Memories Collections Structured prefinished hardwood flooring Micro-V bevel (on 4 sides) Incomparable tongue and groove fit for remarkable uniformity 										
Thickness	3/4" (Sawn hardwood layer 5/32", SPF Quarter sawn core layer 17/32" and wood backing board 1/16")										
Width	5"										
Length	30"										
Installation	Glued down (above, on or below grade)										
Subfloor	Wood, concrete or radiant heat system										
Species	4 species: Maple, Red Oak, White Oak, Hickory										
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. ⚠ Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 										
Color choice (refer to 2021 Mirage Collections)	16 colors: Bubble Bath, Desert Rose, Gelato, Hopscotch, Hula Hoop, Lunar Eclipse, Natural, Paddle Ball, Peppermint, Roller Coaster, Sailing Stone, Sand Castle, Sandy Reef, Snowdrift, Stardust, White Mist. Some products may not be available. Ask your Mirage representative or consult the product chart.										
Finish	<ul style="list-style-type: none"> DuraMatt® (5% gloss): Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5 										
Applicable standards	<table border="0"> <tr> <td> Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 90 Class C • SD (Smoke Development) 80 </td> <td> Surface Burning (ULC-S-102-2): • FSR (Flame Spread Rating) 107 • SDC (Smoke Development Classification) 311 </td> </tr> <tr> <td> Critical radiant flux (ASTM-E-648-94a): 0.38 watt/cm² (depends on wood species) </td> <td> R value: R 0.86 to 0.89 (depends on wood species) </td> </tr> <tr> <td colspan="2"> Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (TruBalance) conform </td> </tr> </table>	Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 90 Class C • SD (Smoke Development) 80	Surface Burning (ULC-S-102-2): • FSR (Flame Spread Rating) 107 • SDC (Smoke Development Classification) 311	Critical radiant flux (ASTM-E-648-94a): 0.38 watt/cm ² (depends on wood species)	R value: R 0.86 to 0.89 (depends on wood species)	Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (TruBalance) conform					
Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 90 Class C • SD (Smoke Development) 80	Surface Burning (ULC-S-102-2): • FSR (Flame Spread Rating) 107 • SDC (Smoke Development Classification) 311										
Critical radiant flux (ASTM-E-648-94a): 0.38 watt/cm ² (depends on wood species)	R value: R 0.86 to 0.89 (depends on wood species)										
Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (TruBalance) conform											
Provenance	Made in St-Georges, Qc, Canada.										
Use	Residential, light commercial or commercial										
Accessories	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round										
Warranty	<table border="0"> <tr> <td> <ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must be maintained within a range of 25% and 80%). </td> <td> <ul style="list-style-type: none"> 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications </td> </tr> </table>	<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must be maintained within a range of 25% and 80%). 	<ul style="list-style-type: none"> 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 								
<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must be maintained within a range of 25% and 80%). 	<ul style="list-style-type: none"> 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 										
Patterns	<table border="0"> <tr> <td> <ul style="list-style-type: none"> Herringbone Basket Double Herringbone </td> <td> <ul style="list-style-type: none"> Cube English pattern (bricks) Fence </td> </tr> </table>	<ul style="list-style-type: none"> Herringbone Basket Double Herringbone 	<ul style="list-style-type: none"> Cube English pattern (bricks) Fence 								
<ul style="list-style-type: none"> Herringbone Basket Double Herringbone 	<ul style="list-style-type: none"> Cube English pattern (bricks) Fence 										
Packaging	Length: 30"										
Content of a box	• 16.67 sq. ft.										
Size of a box	• 61-1/4" L x 10-3/4" W x 3-1/4" H										
Weight of a box	• 28 to 32 lbs										
Content of a pallet	• 40 boxes = 666.8 sq. ft. (4 boxes/W x 10 boxes/H)										
Size of a pallet	• 61-1/4" L x 42-1/2" W x 36" H										
Relative species hardness	<table border="0"> <tr> <td>• Walnut</td> <td>1,010 lbs - 22% softer</td> </tr> <tr> <td>• Red Oak</td> <td>1,290 lbs - average harder</td> </tr> <tr> <td>• White Oak</td> <td>1,360 lbs - 5% harder</td> </tr> <tr> <td>• Maple</td> <td>1,450 lbs - 12% harder</td> </tr> <tr> <td>• Hickory</td> <td>1,820 lbs - 41% harder</td> </tr> </table>	• Walnut	1,010 lbs - 22% softer	• Red Oak	1,290 lbs - average harder	• White Oak	1,360 lbs - 5% harder	• Maple	1,450 lbs - 12% harder	• Hickory	1,820 lbs - 41% harder
• Walnut	1,010 lbs - 22% softer										
• Red Oak	1,290 lbs - average harder										
• White Oak	1,360 lbs - 5% harder										
• Maple	1,450 lbs - 12% harder										
• Hickory	1,820 lbs - 41% harder										

* Cashmere is a registered trademark used under license.