



Characteristics	Mirage Classic		
	Natural Collection		
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) 		
Thickness	3/4" (19 mm)		
Length	Random lengths (from 10" (250 mm) to 76" (1,930 mm))		
Width	2-1/4" (57 mm)	2-1/2" (64 mm) and 3-1/4" (83 mm)	4-1/4" (108 mm)
Species	3 species: Maple, Yellow Birch, Red Oak		
Grade	<ul style="list-style-type: none"> • Select & Better (Selection of more uniform wood grain with slight variations in natural shading) • Exclusive (As found in nature. A complete species color and character range) 		
Color choice (refer to 2017 Mirage Collections)	1 color: Natural Some products may not be available. Ask your Mirage representative or consult the product chart.		
Finish	<ul style="list-style-type: none"> • Nanolinx™ HD: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • Nanolinx™ Commercial: Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • Semi-gloss (50% gloss) or Cashmere®* (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55		
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 (depends on wood species) • Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm² (depends on wood species) R value: R 0.6 to 0.8 (depends on wood species)		
Installation	Nailed or stapled down (above and on grade)		
Subfloor	Wood		
Provenance	Made in St-Georges, Qc, Canada.		
Use	Residential or light commercial		
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round		
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications 		
Packaging	2-1/4" (57 mm)	2-1/2" (64 mm) and 3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft² (1.858 m²)	• 20 ft² (1.858 m²)	• 18 ft² (1.672 m²)
Size of a box	• 86" L x 9-1/2" W x 3-1/4" H	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft² (4 boxes/W x 12 boxes/H)	• 48 boxes = 960 ft² (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 ft² (4 boxes/W x 12 boxes/H)
Size of a pallet	• 86" L x 38" W x 43" H	• 79" L x 42" W x 43" H	• 85-1/2" L x 38" W x 43" H
Relative species hardness			
NWFA Janka Test	<ul style="list-style-type: none"> • Walnut 1,010 lbs - 22% softer • Yellow Birch 1,260 lbs - 2% softer • Red Oak 1,290 lbs - average hardness • Maple 1,450 lbs - 12% harder 		
Hardness test (ASTM-D-143)			
Red Oak 1290 lbs* - 100%			
*lbs = Applied force in pounds			

* Cashmere is a registered trademark used under license.



Characteristics	Mirage Classic		
	Admiration Collection		
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) 		
Thickness	3/4" (19 mm)		
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))		
Width	2-1/4" (57 mm)	2-1/2" (64 mm) and 3-1/4" (83 mm)	4-1/4" (108 mm)
Species	3 species: Maple, Yellow Birch, Red Oak		
Grade	• Exclusive (As found in nature. A complete species color and character range)		
Color choice (refer to 2017 Mirage Collections)	24 colors: Nordic, Cape Cod, Rio, Greystone, Platinum, Charcoal, Graphite, Java, Coffee, Waterloo, Vienna, Bolton, Umbria, Havana, Rich Oak, Savanna, Hudson, North Hatley, Sierra, Golden, Windsor, Nevada, Auburn, Canyon Some products may require a minimum quantity or may not be available. Ask your Mirage representative or consult the product chart.		
Finish	<ul style="list-style-type: none"> • Nanolinx™ HD: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • Nanolinx™ Commercial: Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • Semi-gloss (50% gloss) or Cashmere®* (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55		
Applicable standards	Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species) Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) R value: R 0.6 to 0.8 (depends on wood species)		
Installation	Nailed or stapled down (above and on grade)		
Subfloor	Wood		
Provenance	Made in St-Georges, Qc, Canada.		
Use	Residential or light commercial		
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round		
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications 		
Packaging	2-1/4" (57 mm)	2-1/2" (64 mm) and 3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft ² (1.858 m ²)	• 20 ft ² (1.858 m ²)	• 18 ft ² (1.672 m ²)
Size of a box	• 86" L x 9-1/2" W x 3-1/4" H	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft ² (4 boxes/W x 12 boxes/H)	• 48 boxes = 960 ft ² (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 ft ² (4 boxes/W x 12 boxes/H)
Size of a pallet	• 86" L x 38" W x 43" H	• 79" L x 42" W x 43" H	• 85-1/2" L x 38" W x 43" H
Relative species hardness			
NWFA Janka Test	• Yellow Birch	1,260 lbs - 2% softer	
Hardness test (ASTM-D-143)	• Red Oak	1,290 lbs - average hardness	
	• Maple	1,450 lbs - 12% harder	
Red Oak 1290 lbs* - 100%			
*lbs = Applied force in pounds			



* Cashmere is a registered trademark used under license.



Characteristics	Mirage Classic		
	Alive Collection		
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) • Brushed 		
Thickness	3/4" (19 mm)		
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))		
Width	2-1/4" (57 mm)	2-1/2" (64 mm) and 3-1/4" (83 mm)	4-1/4" (108 mm)
Species	1 species: Red Oak		
Grade	• Exclusive (As found in nature. A complete species color and character range)		
Color choice (refer to 2017 Mirage Collections)	7 colors : Oakland, Stanford, Farnham, Eastman, Knowlton, Isla, Sepia Some products may not be available. Ask your Mirage representative or consult the product chart.		
Finish	<ul style="list-style-type: none"> • Nanolinx™ HD: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • Cashmere®* (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55		
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 • Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm² (depends on wood species) R value: R 0.6 to 0.8 (depends on wood species)		
Installation	Nailed or stapled down (above and on grade)		
Subfloor	Wood		
Provenance	Made in St-Georges, Qc, Canada.		
Uses	Residential or light commercial		
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round		
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications 		
Packaging	2-1/4" (57 mm)	2-1/2" (64 mm) and 3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft² (1,858 m²)	• 20 ft² (1,858 m²)	• 18 ft² (1,672 m²)
Size of a box	• 86" L x 9-1/2" W x 3-1/4" H	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft²	• 48 boxes = 960 ft²	• 48 boxes = 864 ft²
Size of a pallet	(4 boxes/W x 12 boxes/H) • 86" L x 38" W x 43" H	(4 boxes/W x 12 boxes/H) • 79" L x 42" W x 43" H	(4 boxes/W x 12 boxes/H) • 85-1/2" L x 38" W x 43" H
Relative species hardness	NWFA Janka Test Hardness test (ASTM-D-143) Red Oak 1290 lbs* - 100% *lbs = Applied force in pounds		
	• Red Oak	1,290 lbs - average hardness	



* Cashmere is a registered trademark used under license.



Characteristics	Mirage Classic	
	Sweet Memories Collection 	
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) • An exclusive variable staining process 	
Thickness	3/4" (19 mm)	
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))	
Width	3-1/4" (83 mm)	4-1/4" (108 mm)
Species	1 species: Maple Character	2 species: Maple Character, Yellow Birch Character
Grade	<ul style="list-style-type: none"> •  Character-looking floors: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 	
Color choice (refer to 2017 Mirage Collections)	6 colors: Gelato, Peppermint, Nougat, Praline, Gingerbread, Black Jelly Bean	
Finish	<ul style="list-style-type: none"> • Nanolinx™ HD: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • Cashmere®* (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55	
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 • Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species)	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) R value: R 0.6 to 0.8 (depends on wood species)
	Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform	
Installation	Nailed or stapled down (above and on grade)	
Subfloor	Wood	
Provenance	Made in St-Georges, Qc, Canada.	
Use	Residential or light commercial	
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty • 35-year finish warranty for residential applications 	<ul style="list-style-type: none"> • 3-year finish warranty for light commercial applications
Packaging	3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft ² (1.858 m ²)	• 18 ft ² (1.672 m ²)
Size of a box	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft ² (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 ft ² (4 boxes/W x 12 boxes/H)
Size of a pallet	• 79" L x 42" W x 43" H	• 85-1/2" L x 38" W x 43" H
Relative species hardness		
NWFA Janka Test	• Yellow Birch	1,260 lbs - 2% softer
Hardness test (ASTM-D-143)	• Maple	1,450 lbs - 12% harder
Red Oak 1290 lbs* - 100% *lbs = Applied force in pounds		



* Cashmere is a registered trademark used under license.



Characteristics	Mirage Classic	
	Sweet Memories Collection 	
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) • Antique look, Brushed 	
Thickness	3/4" (19 mm)	
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))	
Width	3-1/4" (83 mm)	4-1/4" (108 mm)
Species	1 species: Red Oak Character	
Grade	<ul style="list-style-type: none"> •  Character-looking floors: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 	
Color choice (refer to 2017 Mirage Collections)	5 colors: Carousel, Château, Treasure, Hopscotch, Tree House	
Finish	<ul style="list-style-type: none"> • Nanolinx™ HD: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • Cashmere®* (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55	
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 • Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species)	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) R value: R 0.6 to 0.8 (depends on wood species)
	Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform	
Installation	Nailed or stapled down (above and on grade)	
Subfloor	Wood	
Provenance	Made in St-Georges, Qc, Canada.	
Use	Residential or light commercial	
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty • 35-year finish warranty for residential applications 	<ul style="list-style-type: none"> • 3-year finish warranty for light commercial applications
Packaging	3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft ² (1.858 m ²)	• 18 ft ² (1.672 m ²)
Size of a box	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft ² (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 ft ² (4 boxes/W x 12 boxes/H)
Size of a pallet	• 79" L x 42" W x 43" H	• 85-1/2" L x 38" W x 43" H
Relative species hardness		
NWFA Janka Test Hardness test (ASTM-D-143)	<ul style="list-style-type: none"> • Red Oak 1,290 lbs - average hardness 	
Red Oak 1290 lbs* - 100% *lbs = Applied force in pounds		



* Cashmere is a registered trademark used under license.



Characteristics	Mirage Classic	
	Imagine Collection 	
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) • Textured 	
Thickness	3/4" (19 mm)	
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))	
Width	3-1/4" (83 mm)	4-1/4" (108 mm)
Species	2 species: Red Oak Character, Maple Character	
Grade	<ul style="list-style-type: none"> •  Character-looking floors: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 	
Color choice (refer to 2017 Mirage Collections)	7 colors (Red Oak): Papyrus, Driftwood, Rock Cliff, Sandstone, Seashell, Barn Wood, Fossil 4 colors (Maple): Papyrus, Driftwood, Rock Cliff, Sandstone	
Finish	<ul style="list-style-type: none"> • Nanolinx™ HD: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • Cashmere* (18% gloss) • DuraMatt™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55	
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species)	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) R value: R 0.6 to 0.8 (depends on wood species)
Installation	Nailed or stapled down (above and on grade)	
Subfloor	Wood	
Provenance	Made in St-Georges, Qc, Canada.	
Use	Residential or light commercial	
Accessory	Textured square stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty • 35-year finish warranty for residential applications 	• 3-year finish warranty for light commercial applications
Packaging	3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft ² (1,858 m ²)	• 18 ft ² (1,672 m ²)
Size of a box	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft ² (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 ft ² (4 boxes/W x 12 boxes/H)
Size of a pallet	• 79" L x 42" W x 43" H	• 85-1/2" L x 38" W x 43" H
Relative species hardness		
NWFA Janka Test	• Red Oak	1,290 lbs - average hardness
Hardness test (ASTM-D-143)	• Maple	1,450 lbs - 12% harder
Red Oak 1290 lbs* - 100%		
*lbs = Applied force in pounds		

* Cashmere is a registered trademark used under license.



Characteristics	Mirage Classic						
	Flair Collection - Character 						
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) • An ultra-matte finish on a character grade 						
Thickness	3/4" (19 mm)						
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))						
Width	4-1/4" (108 mm)						
Species	3 species: Red Oak Character, White Oak Character, plain sawn, Maple Character						
Grade	<ul style="list-style-type: none"> •  Character : These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 						
Color choice (refer to 2017 Mirage Collections)	5 colors (Maple): Snowdrift, Sand Dune, Grey Drizzle, Dark Leaf, Nightfall 1 color (Red Oak): Nightfall 5 colors (White Oak, plain sawn): White Mist, Snowdrift, Sand Dune, Grey Drizzle, Dark Leaf						
Finish	DuraMatt™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55						
Applicable standards	<table border="0"> <tr> <td> Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 100 to 150 • Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) </td> <td> Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) </td> </tr> <tr> <td> Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm² (depends on wood species) </td> <td> R value: R 0.6 to 0.8 (depends on wood species) </td> </tr> <tr> <td colspan="2"> Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform </td> </tr> </table>	Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 100 to 150 • Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species)	Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species)	Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species)	R value: R 0.6 to 0.8 (depends on wood species)	Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform	
Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 100 to 150 • Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species)	Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species)						
Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species)	R value: R 0.6 to 0.8 (depends on wood species)						
Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform							
Installation	Nailed or stapled down (above and on grade)						
Subfloor	Wood						
Provenance	Made in St-Georges, Qc, Canada.						
Use	Residential or light commercial						
Accessory	Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round						
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications 						
Packaging	4-1/4" (108 mm)						
Content of a box	• 18 ft ² (1.672 m ²)						
Size of a box	• 85-1/2" L x 9" W x 3-1/4" H						
Weight of a box	• 45 to 55 lbs						
Content of a pallet	• 48 boxes = 864 ft ² (4 boxes/W x 12 boxes/H)						
Size of a pallet	• 85-1/2" L x 38" W x 43" H						
Relative species hardness							
NWFA Janka Test	• Red Oak 1,290 lbs - average hardness						
Hardness test (ASTM-D-143)	• White Oak, plain sawn 1,360 lbs - 5% harder						
	• Maple 1,450 lbs - 12% harder						
Red Oak 1290 lbs* - 100%							
*lbs = Applied force in pounds							