General **Specifications** miffige





Characteristics	Mirage Engineered			
Description	 For Admiration, Natural, Flair, Sweet Memories, Imagine, Escape and DreamVille Collections Engineered prefinished hardwood flooring with tongues and grooves Micro-V bevel (on 4 sides) 			
Thickness	1/2" (Sawn hardwood layer 5/32", 7-ply plywood base 11/32")			
Width	5"-Escape & Dreamville	5"	6-1/2"	7"
Length	Lengths from 17" to 69"	Lengths from 20" to 82"		
Installation	Nailed, stapled or glued (above, on or below grade)			
Subfloor	Wood, concrete or radiant heat system			
Species	4 species: Maple, Red Oak, White Oak, Walnut			
Grade	 Select & Better: Selection of more uniform wood grain with slight variations in natural shading Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. ♠ Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 			
Color choice (refer to 2021 Mirage Collections)	57 colors: Aspen, Auburn, Black Jelly Bean, Bubble Bath, Canyon, Cape Cod, Carmel, Carousel, Charcoal, Château, Coffee, Cold Springs, Destin, Driftwood, Florence, Gelato, Gingerbread, Golden, Greystone, Graphite, Havana, Hermosa, Hopscotch, Hudson, Hula Hoop, Isla, Key Largo, Laguna, Lunar Eclipse, Maui, Morro Bay, Mystic Island, Natural, Nevada, New Haven, Nordic, North Hatley, Nougat, Papyrus, Park City, Peppermint, Platinum, Praline, Providence, Rio, Rock Cliff, Roller Coaster, Sand Castle, Sandstone, Savanna, Sierra, Snowdrift, Stillwater, Treasure, Tree House, Waterloo, White Mist. Some products may not be available. Ask your Mirage representative or consult the product chart.			
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • DuraMatt* (5% gloss) • DuraMatt* X (10% gloss) • Nanolinx* HD Semi-gloss (50% gloss) or Cashmere** (18% gloss) • Nanolinx* Commercial (18% gloss): Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products			
Applicable standards	Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5 5" - Escape-Dreamville - 5" - 6-1/2" - 7"			
	Surface Burning (ASTM-E-84): FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) SD (Smoke Development) < 400 (depends on wood species) Surface Burning (ULC-S-102-2): FSV (Flame Spread Value) 80 (depends on wood species) SD (Smoke Development) < 350 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm² (depends on wood species) R value: R 0.44 to 0.48 (depends on wood species) Formaldehyde and VOC emissions (CDPH 1.2, 2017): Target product group (Engineered) conform			
Provenance	Made in St-Georges, Qc, Canada.			
Use	Residential, light commercial or commercial (Nanolinx® Commercial)			
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round			
Warranty	 Structural lifetime limited warranty 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 			
Packaging	5"-Escape & Dreamville	5"	6-1/2"	7"
Content of a box Size of a box Weight of a box Content of a pallet Size of a pallet Relative species hardness	28.50 sq. ft. 70-3/4" L x 10-3/4" W x 3-1/4" H 53 lbs 48 boxes = 1,368 sq. ft. (4 boxes/W x 12 boxes/H) 71" L x 43" W x 43" H	• 34.10 sq. ft. • 83" L x 10-1/2" W x 3-1/4" H • 65 to 70 lbs • 32 boxes = 1,091.2 sq. ft. (4 boxes/W x 8 boxes/H) • 83" L x 42" W x 30" H	22.15 sq. ft. 83" L x 7" W x 3-1/4" H 42 to 45 lbs 48 boxes = 1,063.2 sq. ft. (6 boxes/W x 8 boxes/H) 83" L x 42" W x 30" H	 23.8 sq. ft. 83-1/2"Lx7-1/2"Wx3-1/4"H 44 to 47 lbs 50 boxes = 1,190 sq. ft. (5 boxes/W x 10 boxes/H) 83"Lx37-1/2"Wx36"H
NWFA Janka Test Hardness test (ASTM-D-143) Red Oak 1,290 lbs* - 100% *lbs = Applied force in pounds	• Walnut 1,010 lbs - 229 • Red Oak 1,290 lbs - ave • White Oak 1,360 lbs - 5% • Maple 1,450 lbs - 129	rage hardness harder		

^{*} Cashmere is a registered trademark used under license.

Toll free: 1-800-463-1303