



Characteristics	Mirage TruBalance		
Description	<ul style="list-style-type: none"> For Admiration, Natural, Flair, Sweet Memories and Imagine Collections Structured prefinished hardwood flooring Incomparable tongue and groove fit for remarkable uniformity Micro-V bevel (on 4 sides) 		
Thickness	3/4" (Sawn hardwood layer 5/32", SPF Quarter sawn core layer 17/32" and wood backing board 1/16")		
Width	5"	6-1/2"	7-3/4"
Length	Lengths from 20" to 82"		Lengths from 23" to 82"
Installation	Nailed, stapled, glued down or floated installation** (above, on or below grade)		
Subfloor	Wood, concrete or radiant heat system		
Species	5 species: Maple, Red Oak, White Oak, Hickory, Walnut		
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 		
Color choice (refer to 2021 Mirage Collections)	50 colors: Auburn, Black Jelly Bean, Bubble Bath, Canyon, Cape Cod, Carousel, Charcoal, Château, Clay Marbles, Coffee, Desert Rose, Driftwood, Gelato, Gingerbread, Golden, Graphite, Greystone, Havana, Hopscotch, Hudson, Hula Hoop, Isla, Jump Rope, Lunar Eclipse, Natural, Nevada, Nordic, North Hatley, Nougat, Paddle Ball, Papyrus, Peppermint, Platinum, Praline, Rio, Rock Cliff, Rocking Horse, Roller Coaster, Sailing Stone, Sandstone, Sand Castle, Sandy Reef, Savanna, Sierra, Snowdrift, Stardust, Treasure, Tree House, Waterloo, White Mist. Some products may not be available. Ask your Mirage representative or consult the product chart.		
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) Nanolinx® HD Cashmere®* (18% gloss) Nanolinx® Commercial (18% gloss): Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5		
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 90 Class C SD (Smoke Development) 80 Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSR (Flame Spread Rating) 107 SDC (Smoke Development Classification) 311 Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm² (depends on wood species)		
Provenance	Made in St-Georges, Qc, Canada.		
Use	Residential, light commercial or commercial		
Accessories	Round Stair nosing, Square Stair nosing, Round Reducer, Multifunction Reducer, Threshold, "T" molding, Quarter round		
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (For the glued down and nailed/stapled installation relative humidity must be maintained within a range of 25% and 80%. For the floated installation relative humidity must be maintained between 30% and 60%). 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 		
Packaging	5"	6-1/2"	7-3/4"
Content of a box	• 22.70 sq. ft.	• 14.75 sq. ft.	• 17.60 sq. ft.
Size of a box	• 83" L x 10-3/4" W x 3-1/4" H	• 83" L x 7" W x 3-1/4" H	• 83" L x 8-3/8" W x 3-1/4" H
Weight of a box	• 42 to 45 lbs	• 27 to 31 lbs	• 32 to 36 lbs
Content of a pallet	• 48 boxes = 1,089.60 sq. ft. (4 boxes/W x 12 boxes/H)	• 48 boxes = 708 sq. ft. (4 boxes/W x 12 boxes/H)	• 60 boxes = 1,056 sq. ft. (5 boxes/W x 12 boxes/H)
Size of a pallet	• 83" L x 43" W x 42" H	• 83" L x 42" W x 42" H	• 83" L x 41-1/4" W x 36" H
Relative species hardness			
NWFA Janka Test	• Walnut	1,010 lbs - 22% softer	
Hardness test (ASTM-D-143)	• Red Oak	1,290 lbs - average harder	
	• White Oak	1,360 lbs - 5% harder	
Red Oak 1,290 lbs* - 100%	• Maple	1,450 lbs - 12% harder	
*lbs = Applied force in pounds	• Hickory	1,820 lbs - 41% harder	

* Cashmere is a registered trademark used under license.

** For floated installation, please review the TruBalance installation Guide available on Mirage website in the Guides and support section.