



| Characteristics | Mirage Classic | |
|--|---|---|
| Description | <ul style="list-style-type: none"> • For Admiration, Natural, Flair, Sweet Memories, Imagine and Escape Collections • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) | |
| Thickness | 3/4" | |
| Width | 3-1/4" | 4-1/4" |
| Length | Random lengths from 10" to 76" | |
| Installation | Nailed or stapled down (above and on grade) | |
| Subfloor | Wood | |
| Species | 3 species: Maple, Red Oak, White Oak | |
| Grade | <ul style="list-style-type: none"> • Select & Better: Selection of more uniform wood grain with slight variations in natural shading • Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. • Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. | |
| Color choice (refer to 2021 Mirage Collections) | 52 colors: Auburn, Black Jelly Bean, Bubble Bath, Canyon, Cape Cod, Carmel, Carousel, Charcoal, Château, Coffee, Cold Springs, Destin, Driftwood, Gelato, Gingerbread, Golden, Greystone, Graphite, Havana, Hopscotch, Hula Hoop, Isla, Jump Rope, Laguna, Lunar Eclipse, Mystic Island, Natural, Nevada, New Haven, Nordic, Nougat, Paddle Ball, Papyrus, Peppermint, Platinum, Praline, Providence, Rio, Rock Cliff, Rocking Horse, Roller Coaster, Sailing Stone, Sand Castle, Sandstone, Savanna, Sierra, Snowdrift, Stardust, Stillwater, Treasure, Tree House, White Mist. Some products may not be available. Ask your Mirage representative or consult the product chart. | |
| Finish | Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> • DuraMatt® (5% gloss) • Nanolinx® HD Semi-gloss (50% gloss) or Cashmere®* (18% gloss) • Nanolinx® Commercial (18% gloss): Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5 | |
| Applicable standards | Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species) Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform | Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) R value: R 0.6 to 0.8 (depends on wood species) |
| Provenance | Made in St-Georges, Qc, Canada. | |
| Use | Residential, light commercial or commercial (Nanolinx® Commercial) | |
| Accessories | Round Stair nosing, Square Stair nosing, Round Reducer, Multifunction reducer, Threshold, "T" molding, Quarter round | |
| Warranty | <ul style="list-style-type: none"> • Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 35% and 55%). | <ul style="list-style-type: none"> • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications • 5-year finish warranty for commercial applications with Nanolinx® Commercial |
| Packaging | 3-1/4" | 4-1/4" |
| Content of a box | • 20 sq. ft. | • 18 sq. ft. |
| Size of a box | • 79" L x 10-1/2" W x 3-1/4" H | • 85-1/2" L x 9" W x 3-1/4" H |
| Weight of a box | • 49 to 60 lbs | • 45 to 55 lbs |
| Content of a pallet | • 48 boxes = 960 sq. ft. (4 boxes/W x 12 boxes/H) | • 48 boxes = 864 sq. ft. (4 boxes/W x 12 boxes/H) |
| Size of a pallet | • 79" L x 42" W x 42" H | • 85-1/2" L x 37" W x 42" H |
| Relative species hardness | | |
| NWFA Janka Test | • Red Oak | 1,290 lbs - average hardness |
| Hardness test (ASTM-D-143) | • White Oak | 1,360 lbs - 5% harder |
| | • Maple | 1,450 lbs - 12% harder |
| Red Oak 1290 lbs* - 100% | | |
| *lbs = Applied force in pounds | | |

* Cashmere is a registered trademark used under license.