



Characteristics	Mirage Classic		
	Natural Collection		
Description	<ul style="list-style-type: none"> <li>• Solid prefinished hardwood flooring with tongues and grooves</li> <li>• Micro-V bevel (on 4 sides)</li> </ul>		
Thickness	3/4" (19 mm)		
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))		
Width	2-1/4" (57 mm)	2-1/2" (64 mm) and 3-1/4" (83 mm)	4-1/4" (108 mm)
Species	4 species: Maple, Yellow Birch, Red Oak, Walnut		
Grade	<ul style="list-style-type: none"> <li>• Select &amp; Better (Selection of more uniform wood grain with slight variations in natural shading)</li> <li>• Exclusive (As found in nature. A complete species color and character range)</li> </ul>		
Color choice (refer to 2017 Mirage Collections)	1 color: Natural Some products may not be available. Ask your Mirage representative or consult the product chart.		
Finish	<ul style="list-style-type: none"> <li>• Nanolinx HD™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane.</li> <li>• Semi-gloss (50% gloss) or Cashmere®* (18% gloss)</li> </ul>		
	UV Protection: All products		Formaldehyde: Free
	Water and solvent: No trace		
	Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55		
Applicable standards	<b>Surface Burning (ASTM-E-84):</b> <ul style="list-style-type: none"> <li>• FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species)</li> <li>• SD (Smoke Development) 75 to 400 (depends on wood species)</li> </ul>		<b>Surface Burning (ULC-S-102-2):</b> <ul style="list-style-type: none"> <li>• FSV (Flame Spread Value) 100 to 150 (depends on wood species)</li> <li>• SD (Smoke Development) 200 to 300 (depends on wood species)</li> </ul>
	<b>Critical radiant flux (ASTM-E-648-94a):</b> 0.25 to 0.40 watt/cm <sup>2</sup> (depends on wood species)		R value: R 0.6 to 0.8 (depends on wood species)
	Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform		
	Installation: Nailed or stapled down (above and on grade)		
Subfloor	Wood		
Provenance	Made in St-Georges, Qc, Canada.		
Use	Residential or light commercial		
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round		
Warranty	<ul style="list-style-type: none"> <li>• Structural lifetime limited warranty</li> <li>• 35-year finish warranty for residential applications</li> </ul>		<ul style="list-style-type: none"> <li>• 3-year finish warranty for light commercial applications</li> </ul>
Packaging	2-1/4" (57 mm)	2-1/2" (64 mm) and 3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft <sup>2</sup> (1.858 m <sup>2</sup> )	• 20 ft <sup>2</sup> (1.858 m <sup>2</sup> )	• 18 ft <sup>2</sup> (1.672 m <sup>2</sup> )
Size of a box	• 86" L x 9-1/2" W x 3-1/4" H	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft <sup>2</sup> (4 boxes/W x 12 boxes/H)	• 48 boxes = 960 ft <sup>2</sup> (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 ft <sup>2</sup> (4 boxes/W x 12 boxes/H)
Size of a pallet	• 86" L x 38" W x 43" H	• 79" L x 42" W x 43" H	• 85-1/2" L x 38" W x 43" H
Relative species hardness			
NWFA Janka Test	• Walnut	1,010 lbs - 22% softer	
Hardness test (ASTM-D-143)	• Yellow Birch	1,260 lbs - 2% softer	
	• Red Oak	1,290 lbs - average hardness	
	• Maple	1,450 lbs - 12% harder	
	Red Oak 1290 lbs* - 100%		
*lbs = Applied force in pounds			

\* Cashmere is a registered trademark used under license.







Characteristics	Mirage Classic		
	Alive Collection		
Description	<ul style="list-style-type: none"> <li>Solid prefinished hardwood flooring with tongues and grooves</li> <li>Micro-V bevel (on 4 sides)</li> <li>Brushed</li> </ul>		
Thickness	3/4" (19 mm)		
Length	Random lengths (from 10" (250 mm) to 76" (1,930 mm))		
Width	2-1/4" (57 mm)	2-1/2" (64 mm) and 3-1/4" (83 mm)	4-1/4" (108 mm)
Species	1 species: Red Oak		
Grade	Exclusive (As found in nature. A complete species color and character range)		
Color choice (refer to 2017 Mirage Collections)	7 colors : Oakland, Stanford, Farnham, Eastman, Knowlton, Isla, Sepia Some products may not be available. Ask your Mirage representative or consult the product chart.		
Finish	<ul style="list-style-type: none"> <li>Nanolinx HD™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane.</li> <li>Cashmere®* (18% gloss)</li> </ul>		
	UV Protection: All products		Formaldehyde: Free
	Water and solvent: No trace		
	Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55		
Applicable standards	<b>Surface Burning (ASTM-E-84):</b> <ul style="list-style-type: none"> <li>FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species)</li> <li>SD (Smoke Development) 75 to 400 (depends on wood species)</li> </ul>		<b>Surface Burning (ULC-S-102-2):</b> <ul style="list-style-type: none"> <li>FSV (Flame Spread Value) 100 to 150 (depends on wood species)</li> <li>SD (Smoke Development) 200 to 300 (depends on wood species)</li> </ul>
	<b>Critical radiant flux (ASTM-E-648-94a):</b> 0.25 to 0.40 watt/cm <sup>2</sup> (depends on wood species)		<b>R value:</b> R 0.6 to 0.8 (depends on wood species)
	<b>Formaldehyde and VOC emissions (CDPH 1.1, 2010) :</b> Target product group (Classic) conform		
Installation	Nailed or stapled down (above and on grade)		
Subfloor	Wood		
Provenance	Made in St-Georges, Qc, Canada.		
Uses	Residential or light commercial		
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round		
Warranty	<ul style="list-style-type: none"> <li>Structural lifetime limited warranty</li> <li>35-year finish warranty for residential applications</li> </ul>		<ul style="list-style-type: none"> <li>3-year finish warranty for light commercial applications</li> </ul>
Packaging	2-1/4" (57 mm)	2-1/2" (64 mm) and 3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft <sup>2</sup> (1.858 m <sup>2</sup> )	• 20 ft <sup>2</sup> (1.858 m <sup>2</sup> )	• 18 ft <sup>2</sup> (1.672 m <sup>2</sup> )
Size of a box	• 86" L x 9-1/2" W x 3-1/4" H	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft <sup>2</sup> (4 boxes/W x 12 boxes/H)	• 48 boxes = 960 ft <sup>2</sup> (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 ft <sup>2</sup> (4 boxes/W x 12 boxes/H)
Size of a pallet	• 86" L x 38" W x 43" H	• 79" L x 42" W x 43" H	• 85-1/2" L x 38" W x 43" H
Relative species hardness			
NWFA Janka Test	• Red Oak 1,290 lbs - average hardness		
Hardness test (ASTM-D-143)			
Red Oak 1290 lbs* - 100%			
*lbs = Applied force in pounds			



\* Cashmere is a registered trademark used under license.



Characteristics	Mirage Classic	
	Sweet Memories Collection 	
Description	<ul style="list-style-type: none"> <li>• Solid prefinished hardwood flooring with tongues and grooves</li> <li>• Micro-V bevel (on 4 sides)</li> <li>• An exclusive variable staining process</li> </ul>	
Thickness	3/4" (19 mm)	
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))	
Width	3-1/4" (83 mm)	4-1/4" (108 mm)
Species	1 species: Maple Character	2 species: Maple Character, Yellow Birch Character
Grade	<ul style="list-style-type: none"> <li>•  <b>Character-looking floors:</b> These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.</li> </ul>	
Color choice (refer to 2017 Mirage Collections)	6 colors: Gelato, Peppermint, Nougat, Praline, Gingerbread, Black Jelly Bean	
Finish	<ul style="list-style-type: none"> <li>• Nanolinx HD™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane.</li> <li>• Cashmere®* (18% gloss)</li> </ul>	
	UV Protection: All products	Formaldehyde: Free
	Water and solvent: No trace	
	Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55	
Applicable standards	<b>Surface Burning (ASTM-E-84):</b> <ul style="list-style-type: none"> <li>• FSI (Flame Spread Index) 100 to 150</li> <li>• Classe C (depends on wood species)</li> <li>• SD (Smoke Development) 75 to 400 (depends on wood species)</li> </ul>	
	<b>Surface Burning (ULC-S-102-2):</b> <ul style="list-style-type: none"> <li>• FSV (Flame Spread Value) 100 to 150 (depends on wood species)</li> <li>• SD (Smoke Development) 200 to 300 (depends on wood species)</li> </ul>	
	<b>Critical radiant flux (ASTM-E-648-94a):</b> 0.25 to 0.40 watt/cm <sup>2</sup> (depends on wood species)	R value: R 0.6 to 0.8 (depends on wood species)
	Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform	
Installation	Nailed or stapled down (above and on grade)	
Subfloor	Wood	
Provenance	Made in St-Georges, Qc, Canada.	
Use	Residential or light commercial	
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> <li>• Structural <b>lifetime</b> limited warranty</li> <li>• <b>35-year</b> finish warranty for residential applications</li> </ul>	<ul style="list-style-type: none"> <li>• <b>3-year</b> finish warranty for light commercial applications</li> </ul>
Packaging	3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft <sup>2</sup> (1,858 m <sup>2</sup> )	• 18 ft <sup>2</sup> (1,672 m <sup>2</sup> )
Size of a box	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft <sup>2</sup> (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 ft <sup>2</sup> (4 boxes/W x 12 boxes/H)
Size of a pallet	• 79" L x 42" W x 43" H	• 85-1/2" L x 38" W x 43" H
Relative species hardness		
NWFA Janka Test	• Yellow Birch	1,260 lbs - 2% softer
Hardness test (ASTM-D-143)	• Maple	1,450 lbs - 12% harder
Red Oak 1290 lbs* - 100%		
*lbs = Applied force in pounds		



\* Cashmere is a registered trademark used under license.



Characteristics	Mirage Classic	
	Sweet Memories Collection 	
Description	<ul style="list-style-type: none"> <li>• Solid prefinished hardwood flooring with tongues and grooves</li> <li>• Micro-V bevel (on 4 sides)</li> <li>• Antique look, Brushed</li> </ul>	
Thickness	3/4" (19 mm)	
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))	
Width	3-1/4" (83 mm)	4-1/4" (108 mm)
Species	1 species: Red Oak Character	
Grade	<ul style="list-style-type: none"> <li>•  <b>Character-looking floors:</b> These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.</li> </ul>	
Color choice (refer to 2017 Mirage Collections)	5 colors: Carousel, Château, Treasure, Hopscotch, Tree House	
Finish	<ul style="list-style-type: none"> <li>• Nanolinx HD™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane.</li> <li>• Cashmere®* (18% gloss)</li> </ul>	
	UV Protection: All products	Formaldehyde: Free
	Water and solvent: No trace	
	Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55	
Applicable standards	<p>Surface Burning (ASTM-E-84):</p> <ul style="list-style-type: none"> <li>• FSI (Flame Spread Index) 100 to 150</li> <li>• Classe C (depends on wood species)</li> <li>• SD (Smoke Development) 75 to 400 (depends on wood species)</li> </ul> <p>Critical radiant flux (ASTM-E-648-94a):</p> <p>0.25 to 0.40 watt/cm<sup>2</sup> (depends on wood species)</p> <p>Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform</p>	
	<p>Surface Burning (ULC-S-102-2):</p> <ul style="list-style-type: none"> <li>• FSV (Flame Spread Value) 100 to 150 (depends on wood species)</li> <li>• SD (Smoke Development) 200 to 300 (depends on wood species)</li> </ul> <p>R value: R 0.6 to 0.8 (depends on wood species)</p>	
Installation	Nailed or stapled down (above and on grade)	
Subfloor	Wood	
Provenance	Made in St-Georges, Qc, Canada.	
Use	Residential or light commercial	
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> <li>• Structural lifetime limited warranty</li> <li>• 35-year finish warranty for residential applications</li> </ul>	<ul style="list-style-type: none"> <li>• 3-year finish warranty for light commercial applications</li> </ul>
Packaging	3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft <sup>2</sup> (1.858 m <sup>2</sup> )	• 18 ft <sup>2</sup> (1.672 m <sup>2</sup> )
Size of a box	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 45 to 55 lbs
Content of a pallet	• 48 boxes = 960 ft <sup>2</sup>	• 48 boxes = 864 ft <sup>2</sup>
	(4 boxes/W x 12 boxes/H)	(4 boxes/W x 12 boxes/H)
Size of a pallet	• 79" L x 42" W x 43" H	• 85-1/2" L x 38" W x 43" H
Relative species hardness		
NWFA Janka Test	• Red Oak	1,290 lbs - average hardness
Hardness test (ASTM-D-143)		
Red Oak 1290 lbs* - 100%		
*lbs = Applied force in pounds		

\* Cashmere is a registered trademark used under license.





Characteristics	Mirage Classic			
	Imagine Collection 			
Description	<ul style="list-style-type: none"> <li>• Solid prefinished hardwood flooring with tongues and grooves</li> <li>• Micro-V bevel (on 4 sides)</li> <li>• Textured</li> </ul>			
Thickness	3/4" (19 mm)			
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))			
Width	3-1/4" (83 mm)	4-1/4" (108 mm)		
Species	2 species: Red Oak Character, Maple Character			
Grade	<ul style="list-style-type: none"> <li>•  <b>Character-looking floors:</b> These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.</li> </ul>			
Color choice (refer to 2017 Mirage Collections)	7 colors (Red Oak): Papyrus, Driftwood, Rock Cliff, Sandstone, Seashell, Barn Wood, Fossil 4 colors (Maple): Papyrus, Driftwood, Rock Cliff, Sandstone			
Finish	<ul style="list-style-type: none"> <li>• Nanolinx HD™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane.</li> <li>• Cashmere®* (18% gloss)</li> <li>• DuraMatt™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane.</li> </ul> UV Protection: All products <span style="float: right;">Formaldehyde: Free</span> Water and solvent: No trace Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55			
Applicable standards	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%; vertical-align: top;"> <b>Surface Burning (ASTM-E-84):</b>                              • FSI (Flame Spread Index) 100 to 150                                Classe C (depends on wood species)                              • SD (Smoke Development) 75 to 400 (depends on wood species)   <b>Critical radiant flux (ASTM-E-648-94a):</b>                              0.25 to 0.40 watt/cm<sup>2</sup> (depends on wood species)   <b>Formaldehyde and VOC emissions (CDPH 1.1, 2010) :</b> Target product group (Classic) conform                         </td> <td style="width: 50%; vertical-align: top;"> <b>Surface Burning (ULC-S-102-2):</b>                              • FSV (Flame Spread Value) 100 to 150 (depends on wood species)                              • SD (Smoke Development) 200 to 300 (depends on wood species)   <b>R value:</b> R 0.6 to 0.8 (depends on wood species)                         </td> </tr> </table>		<b>Surface Burning (ASTM-E-84):</b> • FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species)  <b>Critical radiant flux (ASTM-E-648-94a):</b> 0.25 to 0.40 watt/cm <sup>2</sup> (depends on wood species)  <b>Formaldehyde and VOC emissions (CDPH 1.1, 2010) :</b> Target product group (Classic) conform	<b>Surface Burning (ULC-S-102-2):</b> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species)  <b>R value:</b> R 0.6 to 0.8 (depends on wood species)
<b>Surface Burning (ASTM-E-84):</b> • FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species)  <b>Critical radiant flux (ASTM-E-648-94a):</b> 0.25 to 0.40 watt/cm <sup>2</sup> (depends on wood species)  <b>Formaldehyde and VOC emissions (CDPH 1.1, 2010) :</b> Target product group (Classic) conform	<b>Surface Burning (ULC-S-102-2):</b> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species)  <b>R value:</b> R 0.6 to 0.8 (depends on wood species)			
Installation	Nailed or stapled down (above and on grade)			
Subfloor	Wood			
Provenance	Made in St-Georges, Qc, Canada.			
Use	Residential or light commercial			
Accessory	Textured square stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round			
Warranty	<ul style="list-style-type: none"> <li>• Structural <b>lifetime</b> limited warranty</li> <li>• <b>35-year</b> finish warranty for residential applications</li> <li>• <b>3-year</b> finish warranty for light commercial applications</li> </ul>			
Packaging	3-1/4" (83 mm)	4-1/4" (108 mm)		
Content of a box	• 20 ft <sup>2</sup> (1.858 m <sup>2</sup> )			
Size of a box	• 79" L x 10-1/2" W x 3-1/4" H	• 18 ft <sup>2</sup> (1.672 m <sup>2</sup> )		
Weight of a box	• 49 to 60 lbs	• 85-1/2" L x 9" W x 3-1/4" H		
Content of a pallet	• 48 boxes = 960 ft <sup>2</sup> (4 boxes/W x 12 boxes/H)			
Size of a pallet	• 79" L x 42" W x 43" H	• 45 to 55 lbs		
		• 48 boxes = 864 ft <sup>2</sup> (4 boxes/W x 12 boxes/H)		
		• 85-1/2" L x 38" W x 43" H		
Relative species hardness				
NWFA Janka Test	• Red Oak	1,290 lbs - average hardness		
Hardness test (ASTM-D-143)	• Maple	1,450 lbs - 12% harder		
Red Oak 1290 lbs* - 100%				
*lbs = Applied force in pounds				

\* Cashmere is a registered trademark used under license.





Characteristics		Mirage Classic
Flair Collection - Character 		
Description	<ul style="list-style-type: none"> <li>Solid prefinished hardwood flooring with tongues and grooves</li> <li>Micro-V bevel (on 4 sides)</li> <li>An ultra-matte finish on a character grade</li> </ul>	
Thickness	3/4" (19 mm)	
Length	Random lengths (from 10" (250 mm) to 76" (1,930 mm))	
Width	4-1/4" (108 mm)	
Species	3 species: Red Oak Character, White Oak Character, plain sawn, Maple Character	
Grade	<ul style="list-style-type: none"> <li> <b>Character</b> : These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.</li> </ul>	
Color choice <small>(refer to 2017 Mirage Collections)</small>	5 colors (Maple): Snowdrift, Sand Dune, Grey Drizzle, Dark Leaf, Nightfall     1 color (Red Oak): Nightfall 5 colors (White Oak, plain sawn): White Mist, Snowdrift, Sand Dune, Grey Drizzle, Dark Leaf	
Finish	DuraMatt™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane.	
	UV Protection: All products	Formaldehyde: Free
	Water and solvent: No trace	
	Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55	
Applicable standards	Surface Burning (ASTM-E-84):	Surface Burning (ULC-S-102-2):
	<ul style="list-style-type: none"> <li>FSI (Flame Spread Index) 100 to 150</li> <li>Classe C (depends on wood species)</li> <li>SD (Smoke Development) 75 to 400 (depends on wood species)</li> </ul>	<ul style="list-style-type: none"> <li>FV (Flame Spread Value) 100 to 150 (depends on wood species)</li> <li>SD (Smoke Development) 200 to 300 (depends on wood species)</li> </ul>
	Critical radiant flux (ASTM-E-648-94a):	R value: R 0.6 to 0.8 (depends on wood species)
	0.25 to 0.40 watt/cm <sup>2</sup> (depends on wood species)	
	Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform	
Installation	Nailed or stapled down (above and on grade)	
Subfloor	Wood	
Provenance	Made in St-Georges, Qc, Canada.	
Use	Residential or light commercial	
Accessory	Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> <li>Structural <b>lifetime</b> limited warranty</li> <li>35-year finish warranty for residential applications</li> </ul>	<ul style="list-style-type: none"> <li>3-year finish warranty for light commercial applications</li> </ul>
Packaging	4-1/4" (108 mm)	
Content of a box	18 ft <sup>2</sup> (1.672 m <sup>2</sup> )	
Size of a box	85-1/2" L x 9" W x 3-1/4" H	
Weight of a box	45 to 55 lbs	
Content of a pallet	48 boxes = 864 ft <sup>2</sup> (4 boxes/W x 12 boxes/H)	
Size of a pallet	85-1/2" L x 38" W x 43" H	
<b>Relative species hardness</b>		
NWFA Janka Test	Red Oak	1,290 lbs - average hardness
Hardness test (ASTM-D-143)	White Oak, plain sawn	1,360 lbs - 5% harder
	Maple	1,450 lbs - 12% harder
	Red Oak 1290 lbs* - 100%	
*lbs = Applied force in pounds		