



Characteristics	Mirage Classic	
	Imagine Collection	
Description	<ul style="list-style-type: none"> <li>• Solid prefinished hardwood flooring with tongues and grooves</li> <li>• Micro-V bevel (on 4 sides)</li> <li>• Textured</li> </ul>	
Thickness	3/4" (19 mm)	
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))	
Width	3-1/4" (83 mm)	4-1/4" (108 mm)
Species	2 species: Old Red Oak, Old Maple	
Grade	<ul style="list-style-type: none"> <li>• Old Maple (These floors present pronounced color variations, repaired and sound knots, surface holes, hairline cracks, mineral streaks, and other character or milling marks)</li> <li>• Old Red Oak (These floors present pronounced color variations, open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment)</li> </ul>	
Color choice (refer to 2016 Mirage Collections)	6 colors: Papyrus, Rock Cliff, Seashell, Barn Wood, Sandstone, Fossil	
Finish	<ul style="list-style-type: none"> <li>• Nanolinx HD™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane.</li> <li>• Cashmere®* (18% gloss)</li> </ul>	
	UV Protection: All products	Formaldehyde: Free
	Water and solvent: No trace	
	Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55	
Applicable standards	Surface Burning (ASTM-E-84):	Surface Burning (ULC-S-102-2):
	• FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species)	• FSC (Flame Spread Classification) 100 to 150 (depends on wood species)
	• SD (Smoke Development) 75 to 400 (depends on wood species)	• SD (Smoke Development) 200 to 300 (depends on wood species)
	Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm <sup>2</sup> (depends on wood species)	R value: R 0.6 to 0.8 (depends on wood species)
	Formaldehyde emission (ASTM-E-1333-02):	Total VOC (ASTM-D-6670-01):
	• Less than 0.01 ppm	• 0.003 ppm (depends on wood species)
Installation	Nailed or stapled down (above and on grade)	
Subfloor	Wood	
Provenance	Made in St-Georges, Qc, Canada.	
Certification	FSC® available on Maple and Red Oak.	
Use	Residential or light commercial	
Accessory	Textured square stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round	
Warranty	<ul style="list-style-type: none"> <li>• Structural lifetime limited warranty</li> <li>• 35-year finish warranty for residential applications</li> </ul>	<ul style="list-style-type: none"> <li>• 3-year finish warranty for light commercial applications</li> </ul>
Packaging	3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 ft <sup>2</sup> (1.858 m <sup>2</sup> )	• 18 ft <sup>2</sup> (1.672 m <sup>2</sup> )
Size of a box	• 79" L x 10-1/2" W x 3-1/4" H	• 82" L x 9" W x 3-1/4" H
Weight of a box	• 49 to 60 lbs	• 49 to 51 lbs
Content of a pallet	• 48 boxes = 960 ft <sup>2</sup> (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 ft <sup>2</sup> (4 boxes/W x 12 boxes/H)
Size of a pallet	• 79" L x 42" W x 43" H	• 82" L x 38" W x 43" H
Relative species hardness		
NWFA Janka Test	• Red Oak	1,290 lbs - average hardness
Hardness test (ASTM-D-143)	• Maple	1,450 lbs - 12% harder
Red Oak 1290 lbs* - 100%		
*lbs = Applied force in pounds		

\* Cashmere is a registered trademark used under license.