



Characteristics	Mirage Classic		
Description	<ul style="list-style-type: none">• Solid prefinished hardwood flooring with tongues and grooves• Micro-V bevel (on 4 sides)		
Thickness	3/4" (19 mm)		
Width	2-1/4" (57 mm)	3-1/4" (83 mm)	4-1/4" (108 mm)
Length¹	Random lengths from 10" (250 mm) to 76" (1,930 mm)		
Installation	Nailed or stapled down (above and on grade)		
Subfloor	Wood		
Species	3 species: Maple, Red Oak, White Oak		
Grade	<ul style="list-style-type: none">• Select & Better: Selection of more uniform wood grain with slight variations in natural shading.• Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation.• ▲ Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.		
Color choice (Refer to 2023 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart .		
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane.		
	<ul style="list-style-type: none">• DuraMatt® (5% gloss)• Nanolinx® HD<ul style="list-style-type: none">• Cashmere®* (18% gloss)• Nanolinx® Commercial (18% gloss)		
	UV Protection: All products		
	Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5		
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none">• FSI (Flame Spread Index) 100 to 150<ul style="list-style-type: none">Class C (depends on wood species)• SD (Smoke Development) 75 to 400 (depends on wood species)		Surface Burning (ULC-S-102-2): <ul style="list-style-type: none">• FSV (Flame Spread Value) 100 to 150 (depends on wood species)• SD (Smoke Development) 200 to 300 (depends on wood species)
	Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm² (depends on wood species)		R value: R 0.6 to 0.8 (depends on wood species)
	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Classic) conform		
Provenance	Made in St-Georges, Qc, Canada.		
Use	Residential, light commercial or commercial (Nanolinx® Commercial)		
Accessory	Round Stair nosing, Square Stair nosing, Round reducer, Threshold, "T" molding, Quarter round		
Warranty	<ul style="list-style-type: none">• Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 35% and 55%).• 35-year finish warranty for residential applications• 3-year finish warranty for light commercial applications• 5-year finish warranty for commercial applications with Nanolinx® Commercial		
Packaging	2-1/4" (57 mm)	3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	<ul style="list-style-type: none">• 20 sq. ft. (1.86 m²)• 86" L x 9-1/2" W x 3-1/4" H	<ul style="list-style-type: none">• 20 sq. ft. (1.86 m²)• 79" L x 10-1/2" W x 3-1/4" H	<ul style="list-style-type: none">• 18 sq. ft. (1.67 m²)• 85-1/2" L x 9" W x 3-1/4" H
Weight of a box	<ul style="list-style-type: none">• 49 to 60 lbs	<ul style="list-style-type: none">• 49 to 60 lbs	<ul style="list-style-type: none">• 45 to 55 lbs
Content of a pallet	<ul style="list-style-type: none">• 48 boxes = 960 sq. ft. (4 boxes/W x 12 boxes/H)	<ul style="list-style-type: none">• 48 boxes = 960 sq. ft. (4 boxes/W x 12 boxes/H)	<ul style="list-style-type: none">• 48 boxes = 864 sq. ft. (4 boxes/W x 12 boxes/H)
Size of a pallet	<ul style="list-style-type: none">• 86" L x 38" W x 42" H	<ul style="list-style-type: none">• 79" L x 42" W x 42" H	<ul style="list-style-type: none">• 85-1/2" L x 36" W x 42" H
Relative species hardness			
NWFA Janka Test	<ul style="list-style-type: none">• Red Oak	1,290 lbs - average hardness	
Hardness test (ASTM-D-143)	<ul style="list-style-type: none">• White Oak	1,360 lbs - 5% harder	
	<ul style="list-style-type: none">• Maple	1,450 lbs - 12% harder	
Red Oak 1,290 lbs* - 100% *lbs = Applied force in pounds			

* Cashmere is a registered trademark used under license.

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.






Characteristics	Mirage Engineered
Description	<ul style="list-style-type: none"> Engineered prefinished hardwood flooring with tongues and grooves Micro-V bevel (on 4 sides)
Thickness	1/2" (13 mm) (Sawn hardwood layer 5/32" (4 mm), 7-ply plywood base 11/32" (9 mm))
Width	5" (127 mm)
Length ¹	Lengths from 20" (511 mm) to 82" (2,086 mm)
Installation	Nailed, stapled or glued (above, on or below grade)
Subfloor	Wood, concrete or radiant heat system
Species	3 species: Maple, Red Oak, Oak
Grade	<ul style="list-style-type: none"> Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.
Color choice (Refer to 2023 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt[®] X (10% gloss) Nanolinx[®] HD <ul style="list-style-type: none"> Cashmere[®] (18% gloss) Nanolinx[®] Commercial (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) SD (Smoke Development) < 400 (depends on wood species) Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSV (Flame Spread Value) 80 (depends on wood species) SD (Smoke Development) < 350 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm ² (depends on wood species) R value: R 0.44 to 0.48 (depends on wood species) Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Engineered) conform
Provenance	Made in St-Georges, Qc, Canada.
Use	Residential, light commercial or commercial (Nanolinx [®] Commercial)
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round Acoustitech underlayments are recommended by Mirage. To know more about the minimum criteria needed regarding the recommended waterproof acoustic underlayment, please refer to the Technical Newsletter #20 in the Guides and Support section at miragefloors.com .
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 25% and 70%). 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx[®] Commercial
Packaging	5" (127 mm)
Content of a box Size of a box Weight of a box Content of a pallet Size of a pallet	<ul style="list-style-type: none"> 34.10 sq. ft. (3.17 m²) 83" L x 10-1/2" W x 3-1/4" H 65 to 70 lbs 32 boxes = 1,091.20 sq. ft. (4 boxes/W x 8 boxes/H) 83" L x 42" W x 30" H
Relative species hardness	
NWFA Janka Test Hardness test (ASTM-D-143) Red Oak 1,290 lbs* - 100% *lbs = Applied force in pounds	<ul style="list-style-type: none"> Red Oak 1,290 lbs - average hardness Oak 1,290 lbs - average hardness Maple 1,450 lbs - 12% harder

* Cashmere is a registered trademark used under license.

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.



Characteristics	Mirage Lock		
Description	<ul style="list-style-type: none"> • Lock prefinished hardwood flooring • 2G™ angling system on the long side of the board of all widths • 5G™ Fold Down system on the short side of the board of 6-1/2" width • Incomparable tongue and groove fit for remarkable uniformity • Micro-V bevel (on 4 sides) 		
Thickness	7/16" (11 mm) (Sawn hardwood layer 1/16" (1.5 mm), HDF Core 9/32" (7.3 mm) and wood backing board)		
Width	4-5/16" (109 mm) 	5" (125 mm) 	6-1/2" (163 mm) 
Length ¹	Lengths from 14" (350 mm) to 46" (1,172 mm)	Lengths from 17" (422 mm) to 69" (1,752 mm)	Lengths from 22" (570 mm) to 69" (1,752 mm)
Installation	Floated over a recommended underlayment or glued down (above, on or below grade)		
Subfloor	Wood, concrete or radiant heat system		
Grade	<ul style="list-style-type: none"> • Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. • Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 		
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> • DuraMatt® (5% gloss) • Nanolinx® HD <ul style="list-style-type: none"> • Cashmere® (18% gloss) 		
	UV Protection: All products		
	Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5		
Applicable standards	<div> Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 85 to 110 • Class C (depends on wood species) • SD (Smoke Development) 220 to 240 (depends on wood species) </div> <div> Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 85 to 90 (depends on wood species) • SD (Smoke Development) 305 to 365 (depends on wood species) </div> <div> Critical radiant flux (ASTM-E-648-94a): <ul style="list-style-type: none"> • 0.46 to 0.47 watt/cm² (depends on wood species) </div> <div> R value: R 0.34 to 0.36 (depends on wood species) </div> <div> Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Lock) conform </div>		
Provenance	Made in St-Georges, Qc, Canada.		
Use	Residential or light commercial		
Accessories	Round Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round, Round Stair Nosing for glued installation, Round Reducer for glued installation and underlayment. Acoustitech underlayments are recommended by Mirage. To know more about the minimum criteria needed regarding the recommended waterproof acoustic underlayment, please refer to the Technical Newsletter #20 in the Guides and Support section at miragefloors.com .		
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 30% and 60%). • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications 		
Packaging	4-5/16" (109 mm)	5" (125 mm)	6-1/2" (163 mm)
Content of a box	• 22 sq. ft. (2.04 m²)	• 32.60 sq. ft. (3.02 m²)	• 24.35 sq. ft. (2.26 m²)
Size of a box	• 48" L x 9-1/2" W x 3-3/4" H	• 71" L x 10-3/4" W x 3-3/4" H	• 71" L x 7-1/2" W x 3-3/4" H
Weight of a box	• 40 to 42 lbs	• 60 to 62 lbs	• 45 to 47 lbs
Content of a pallet	• 40 boxes = 880 sq. ft.	• 36 boxes = 1,173.60 sq. ft.	• 48 boxes = 1,168.80 sq. ft.
Size of a pallet	• (4 boxes/W x 10 boxes/H)	• (4 boxes/W x 9 boxes/H)	• (6 boxes/W x 8 boxes/H)
	• 48" L x 38" W x 40" H	• 71" L x 43" W x 36" H	• 71" L x 45" W x 32" H
Relative species hardness			
NWFA Janka Test			
Hardness test (ASTM-D-143)	<ul style="list-style-type: none"> • Red Oak 1,290 lbs - average hardness • White Oak 1,360 lbs - 5% harder • Maple 1,450 lbs - 12% harder 		
Red Oak 1,290 lbs* - 100%			
*lbs = Applied force in pounds			

General Specifications

mirage™



Characteristics	Mirage TruBalance		
Description	<ul style="list-style-type: none"> Structured prefinished hardwood flooring Incomparable tongue and groove fit for remarkable uniformity Micro-V bevel (on 4 sides) 		
Thickness	3/4" (19 mm) (Sawn hardwood layer 5/32" (4 mm), SPF Quarter sawn core layer 17/32" (13 mm) and wood backing board 1/16" (2 mm))		
Width	5" (127 mm)	6-1/2" (165 mm)	7-3/4" (197 mm)
Length ¹	Lengths from 20" (511 mm) to 82" (2,086 mm)		Lengths from 23" (590 mm) to 82" (2,086 mm)
Installation	Nailed, stapled, glued down or floated installation** (above, on or below grade)		
Subfloor	Wood, concrete or radiant heat system		
Species	5 species: Maple, Red Oak, White Oak, Hickory, Walnut		
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 		
Color choice (Refer to 2023 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart .		
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) Nanolinx® HD <ul style="list-style-type: none"> Cashmere®* (18% gloss) Nanolinx® Commercial (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5		
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 90 Class C SD (Smoke Development) 80 Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSR (Flame Spread Rating) 107 SDC (Smoke Development Classification) 311 Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm² (depends on wood species) Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (TruBalance) conform		
Provenance	Made in St-Georges, Qc, Canada.		
Use	Residential, light commercial or commercial		
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round Acoustitech underlayments are recommended by Mirage. To know more about the minimum criteria needed regarding the recommended waterproof acoustic underlayment, please refer to the Technical Newsletter #20 in the Guides and Support section at miragefloors.com .		
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (For the glued down and nailed/stapled installation relative humidity must be maintained within a range of 25% and 80%. For the floated installation relative humidity must be maintained between 30% and 60%). 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial 		
Packaging	5" (127 mm)	6-1/2" (165 mm)	7-3/4" (197 mm)
Content of a box	• 22.70 sq. ft. (2.11 m²)	• 14.75 sq. ft. (1.45 m²)	• 17.60 sq. ft. (1.64 m²)
Size of a box	• 83" L x 10-1/2" W x 3-1/4" H	• 83" L x 7" W x 3-1/4" H	• 83" L x 8-1/4" W x 3-1/4" H
Weight of a box	• 42 to 45 lbs	• 27 to 31 lbs	• 32 to 36 lbs
Content of a pallet	• 48 boxes = 1,089.60 sq. ft. (4 boxes/W x 12 boxes/H)	• 72 boxes = 1,062.00 sq. ft. (6 boxes/W x 12 boxes/H)	• 60 boxes = 1,056.00 sq. ft. (5 boxes/W x 12 boxes/H)
Size of a pallet	• 83" L x 42" W x 42" H	• 83" L x 42" W x 42" H	• 83" L x 42" W x 42" H
Relative species hardness			
NWFA Janka Test	• Walnut	1,010 lbs - 22% softer	
Hardness test (ASTM-D-143)	• Red Oak	1,290 lbs - average hardness	
	• White Oak	1,360 lbs - 5% harder	
Red Oak 1,290 lbs* - 100%	• Maple	1,450 lbs - 12% harder	
*lbs = Applied force in pounds	• Hickory	1,820 lbs - 41% harder	

* Cashmere is a registered trademark used under license.

** For floated installation, please review the [TruBalance installation Guide](#) available on Mirage website in the [Guides and support section](#).

1. Lengths in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks length.

Toll free : 1-800-463-1303

General Specifications

mirage



Characteristics	Mirage TruBalance
	Herringbone
Description	<ul style="list-style-type: none"> Structured prefinished hardwood flooring Micro-V bevel (on 4 sides) Incomparable tongue and groove fit for remarkable uniformity
Thickness	3/4" (19 mm) (Sawn hardwood layer 5/32" (4 mm), SPF Quarter sawn core layer 17/32" (13 mm) and wood backing board 1/16" (2 mm))
Width	5" (127 mm)
Length	20" (508 mm)
Installation	Glued down (above, on or below grade)
Subfloor	Wood, concrete or radiant heat system
Species	5 species: Maple, Red Oak, White Oak, Hickory, Walnut
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.
Color choice (Refer to 2023 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) Nanolinx® HD <ul style="list-style-type: none"> Cashmere®* (18% gloss) Nanolinx® Commercial (18% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5
Applicable standards	<div> <div> Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 90 Class C SD (Smoke Development) 80 </div> <div> Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSR (Flame Spread Rating) 107 SDC (Smoke Development Classification) 311 </div> </div> Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm² (depends on wood species)
	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (TruBalance) conform
Provenance	Made in St-Georges, Qc, Canada.
Use	Residential, light commercial or commercial
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round Acoustitech underlayments are recommended by Mirage. To know more about the minimum criteria needed regarding the recommended waterproof acoustic underlayment, please refer to the Technical Newsletter #20 in the Guides and Support section at miragefloors.com .
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must be maintained within a range of 25% and 80%). 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial
Patterns	<ul style="list-style-type: none"> Herringbone Basket Double Herringbone Cube English pattern (bricks) Fence
Packaging	5" (127 mm) x 20" (508 mm)
Content of a box	16.67 sq. ft. (1.55 m²)
Size of a box	61-1/4" L x 10-1/2" W x 3-1/4" H
Weight of a box	28 to 32 lbs
Content of a pallet	48 boxes = 800.16 sq. ft. (4 boxes/W x 12 boxes/H)
Size of a pallet	61-1/4" L x 42" W x 42" H
Relative species hardness	
NWFA Janka Test	<ul style="list-style-type: none"> Walnut 1,010 lbs - 22% softer Red Oak 1,290 lbs - average harder White Oak 1,360 lbs - 5% harder Maple 1,450 lbs - 12% harder Hickory 1,820 lbs - 41% harder
Hardness test (ASTM-D-143)	
Red Oak 1,290 lbs* - 100%	
*lbs = Applied force in pounds	

* Cashmere is a registered trademark used under license.

Toll free : 1-800-463-1303

General Specifications

mirage™



Characteristics	Mirage TruBalance
	Chevron
Description	<ul style="list-style-type: none"> Structured prefinished hardwood flooring Micro-V bevel (on 4 sides) Incomparable tongue and groove fit for remarkable uniformity
Thickness	3/4" (19 mm) (Sawn hardwood layer 5/32" (4 mm), SPF Quarter sawn core layer 17/32" (13 mm) and wood backing board 1/16" (2 mm))
Width	5" (127 mm)
Length	24-7/16" (620 mm)
Installation	Glued down (above, on or below grade)
Subfloor	Wood, concrete or radiant heat system
Species	1 species: White Oak
Grade	<ul style="list-style-type: none"> Character: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.
Color choice (Refer to 2023 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> DuraMatt® (5% gloss) UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5
Applicable standards	<div> Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 90 Class C SD (Smoke Development) 80 </div> <div> Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSR (Flame Spread Rating) 107 SDC (Smoke Development Classification) 311 </div> Critical radiant flux (ASTM-E-648-94a): R value: R 0.86 to 0.89 (depends on wood species) 0.38 watt/cm² (depends on wood species)
	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (TruBalance) conform
Provenance	Made in St-Georges, Qc, Canada.
Use	Residential, light commercial or commercial
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round Acoustitech underlayments are recommended by Mirage. To know more about the minimum criteria needed regarding the recommended waterproof acoustic underlayment, please refer to the Technical Newsletter #20 in the Guides and Support section at miragefloors.com .
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must be maintained within a range of 25% and 80%). 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx® Commercial
Recommended	For the installation of Chevron flooring, we recommend maintaining the relative humidity within a range of 35% and 70%. Staying in this range will ensure the pattern and overall look of your floor last over the years. For more information on the installation of Chevron flooring, consult the Installation Guide.
Patterns	
	<ul style="list-style-type: none"> Chevron Spearhead Brooklyn Bridge Leaf line Boardwalk
Packaging	5" (127 mm) x 24-7/16" (620 mm)
Content of a box	13.60 sq. ft. (1.26 m²)
Size of a box	61-1/4" L x 10-1/2" W x 3-1/4" H
Weight of a box	23 to 26 lbs
Content of a pallet	48 boxes = 652.80 sq. ft. (4 boxes/W x 12 boxes/H)
Size of a pallet	61-1/4" L x 42" W x 42" H
Relative species hardness	
NWFA Janka Test Hardness test (ASTM-D-143)	White Oak 1,360 lbs - 5% harder
Red Oak 1,290 lbs* - 100% *lbs = Applied force in pounds	

* Cashmere is a registered trademark used under license.

Toll free : 1-800-463-1303