



Characteristics	Mirage Classic						
	Flair Collection - Light character						
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) • An ultra-matte finish on a light character grade 						
Thickness	3/4" (19 mm)						
Length	• Random lengths (from 10" (250 mm) to 76" (1,930 mm))						
Width	4-1/4" (108 mm)						
Species	2 species: White Oak, plain sawn, Maple						
Grade	Light character floors have fewer natural character marks such as pronounced color variations, open and closed knots, mineral streaks, surface holes and hairline cracks and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. Available on Maple and White Oak, Plain sawn (open grain for White Oak)						
Color choice (refer to 2016 Mirage Collections)	4 colors (Maple): Snowdrift, Sand Dune, Grey Drizzle, Dark Leaf 5 colors (White Oak, plain sawn): White Mist, Snowdrift, Sand Dune, Grey Drizzle, Dark Leaf						
Finish	DuraMatt™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Formaldehyde: Free Water and solvent: No trace Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55						
Applicable standards	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%; vertical-align: top;"> Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 • Classe C (depends on wood species) • SD (Smoke Development) less than 400 (depends on wood species) </td> <td style="width: 50%; vertical-align: top;"> Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSC (Flame Spread Classification) 80 (depends on wood species) • SD (Smoke Development) max 350 (depends on wood species) </td> </tr> <tr> <td style="vertical-align: top;"> Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm² (depends on wood species) </td> <td style="vertical-align: top;"> R value: R 0.44 to 0.51 (depends on wood species) </td> </tr> <tr> <td style="vertical-align: top;"> Formaldehyde emission (ASTM-E-1333-02): • Less than 0.01 ppm </td> <td style="vertical-align: top;"> Total VOC (ASTM-D-6670-01): 0.011 ppm (depends on wood species) </td> </tr> </table>	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 • Classe C (depends on wood species) • SD (Smoke Development) less than 400 (depends on wood species) 	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSC (Flame Spread Classification) 80 (depends on wood species) • SD (Smoke Development) max 350 (depends on wood species) 	Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm ² (depends on wood species)	R value: R 0.44 to 0.51 (depends on wood species)	Formaldehyde emission (ASTM-E-1333-02): • Less than 0.01 ppm	Total VOC (ASTM-D-6670-01): 0.011 ppm (depends on wood species)
Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 • Classe C (depends on wood species) • SD (Smoke Development) less than 400 (depends on wood species) 	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSC (Flame Spread Classification) 80 (depends on wood species) • SD (Smoke Development) max 350 (depends on wood species) 						
Critical radiant flux (ASTM-E-648-94a): 0.41 watt/cm ² (depends on wood species)	R value: R 0.44 to 0.51 (depends on wood species)						
Formaldehyde emission (ASTM-E-1333-02): • Less than 0.01 ppm	Total VOC (ASTM-D-6670-01): 0.011 ppm (depends on wood species)						
Installation	Nailed or stapled down (above and on grade)						
Subfloor	Wood						
Provenance	Made in St-Georges, Qc, Canada.						
Certification	FSC® available on White Oak, plain sawn and Maple.						
Use	Residential or light commercial						
Accessory	Square Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round						
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications 						
Packaging	4-1/4" (108 mm)						
Content of a box	• 18 ft ² (1,672 m ²)						
Size of a box	• 82" L x 9" W x 3-1/4" H						
Weight of a box	• 49 to 51 lbs						
Content of a pallet	• 48 boxes = 864 ft ² (6 boxes/W x 8 boxes/H)						
Size of a pallet	• 82" L x 38" W x 43" H						
Relative species hardness							
NWFA Janka Test	• White Oak, plain sawn 1,360 lbs - 5% harder						
Hardness test (ASTM-D-143)	• Maple 1,450 lbs - 12% harder						
Red Oak 1290 lbs* - 100%							
*lbs = Applied force in pounds							