



Characteristics	Mirage Classic								
Description	<ul style="list-style-type: none"> • For Admiration, Natural, Flair, Sweet Memories and Imagine Collections • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides) 								
Thickness	3/4"								
Width	2-1/4"	3-1/4"	4-1/4"						
Length	Random lengths from 10" to 76"								
Installation	Nailed or stapled down (above and on grade)								
Subfloor	Wood								
Species	4 species: Maple, Red Oak, White Oak and Yellow Birch.								
Grade	<ul style="list-style-type: none"> • Select & Better: Selection of more uniform wood grain with slight variations in natural shading • Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. • Character floors: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 								
Color choice (refer to 2019 Mirage Collections)	49 colors: Nordic, Greystone, Charcoal, Graphite, Isla, Cape Cod, Rio, Savanna, Rich Oak, Havana, Java, Coffee, Sierra, Golden, Nevada, Auburn, Canyon, Umbria, Vienna, Platinum, Natural, White Mist, Snowdrift, Sand Dune, Grey Drizzle, Lunar Eclipse, Nightfall, Bubble Bath, Hula Hoop, Carousel, Sand Castle, Château, Roller Coaster, Gelato, Treasure, Peppermint, Hopscotch, Nougat, Tree House, Praline, Gingerbread, Black Jelly Bean, Driftwood, Rock Cliff, Barn Wood, Papyrus, Seashell, Sandstone, Fossil. Some products may not be available. Ask your Mirage representative or consult the product chart.								
Finish	<ul style="list-style-type: none"> • DuraMatt™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • Nanolinx™ HD: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> • Semi-gloss (50% gloss) or Cashmere®* (18% gloss) • Nanolinx™ Commercial: Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55								
Applicable standards	<table border="0"> <tr> <td> Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) </td> <td> Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) </td> </tr> <tr> <td> Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm² (depends on wood species) </td> <td> R value: R 0.6 to 0.8 (depends on wood species) </td> </tr> <tr> <td colspan="2"> Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform </td> </tr> </table>			Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species)	Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species)	Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species)	R value: R 0.6 to 0.8 (depends on wood species)	Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform	
Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species)	Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species)								
Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species)	R value: R 0.6 to 0.8 (depends on wood species)								
Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Classic) conform									
Provenance	Made in St-Georges, Qc, Canada.								
Use	Residential, light commercial or commercial (Nanolinx™ Commercial)								
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Multifunction reducer, Threshold, "T" molding, Quarter round								
Warranty	<table border="0"> <tr> <td> <ul style="list-style-type: none"> • Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 35% and 55%). </td> <td> <ul style="list-style-type: none"> • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications • 5-year finish warranty for commercial applications with Nanolinx™ Commercial </td> </tr> </table>			<ul style="list-style-type: none"> • Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 35% and 55%). 	<ul style="list-style-type: none"> • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications • 5-year finish warranty for commercial applications with Nanolinx™ Commercial 				
<ul style="list-style-type: none"> • Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 35% and 55%). 	<ul style="list-style-type: none"> • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications • 5-year finish warranty for commercial applications with Nanolinx™ Commercial 								
Packaging	2-1/4"	3-1/4"	4-1/4"						
Content of a box	• 20 ft ²	• 20 ft ²	• 18 ft ²						
Size of a box	• 86" L x 9-1/2" W x 3-1/4" H	• 79" L x 10-1/2" W x 3-1/4" H	• 85-1/2" L x 9" W x 3-1/4" H						
Weight of a box	• 49 to 60 lbs	• 49 to 60 lbs	• 45 to 55 lbs						
Content of a pallet	• 48 boxes = 960 ft ² (4 boxes/W x 12 boxes/H)	• 48 boxes = 960 ft ² (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 ft ² (4 boxes/W x 12 boxes/H)						
Size of a pallet	• 86" L x 38" W x 42" H	• 79" L x 42" W x 42" H	• 85-1/2" L x 37" W x 42" H						
Relative species hardness	<table border="0"> <tr> <td> • Yellow Birch • Red Oak • White Oak • Maple </td> <td> 1,260 lbs - 2% softer 1,290 lbs - average hardness 1,360 lbs - 5% harder 1,450 lbs - 12% harder </td> </tr> </table>			• Yellow Birch • Red Oak • White Oak • Maple	1,260 lbs - 2% softer 1,290 lbs - average hardness 1,360 lbs - 5% harder 1,450 lbs - 12% harder				
• Yellow Birch • Red Oak • White Oak • Maple	1,260 lbs - 2% softer 1,290 lbs - average hardness 1,360 lbs - 5% harder 1,450 lbs - 12% harder								
NWFA Janka Test	• Yellow Birch 1,260 lbs - 2% softer								
Hardness test (ASTM-D-143)	• Red Oak 1,290 lbs - average hardness								
Red Oak 1290 lbs* - 100%	• White Oak 1,360 lbs - 5% harder								
*lbs = Applied force in pounds	• Maple 1,450 lbs - 12% harder								

* Cashmere is a registered trademark used under license.



Characteristics	Mirage Engineered					
Description	<ul style="list-style-type: none"> For Admiration, Natural, Exotic, Flair, Sweet Memories and Imagine Collections Engineered prefinished hardwood flooring with tongues and grooves Micro-V bevel (on 4 sides) 					
Thickness	3/8" (Sawn hardwood layer 5/32", 5-ply plywood base 15/64")		1/2" (Sawn hardwood layer 5/32", 7-ply plywood base 11/32")		3/4" (Sawn hardwood layer 5/32", 11-ply plywood base 19/32")	
Width	2-9/16"	3-5/16"	5"	6-1/2"	7-3/4"	
Length	Lengths from 14" to 46"			Lengths from 20" to 82"		Lengths from 23" to 82"
Installation	Nailed, stapled or glued (above, on or below grade)			Nailed, stapled, glued or floated** (above, on or below grade)		Nailed, glued or floated** (above, on or below grade)
Subfloor	Wood, concrete or radiant heat system					
Species	9 species: Maple, Red Oak, White Oak, Yellow Birch, Hickory, Walnut, Brazilian Cherry, African Mahogany and Sapele.					
Grade	<ul style="list-style-type: none"> Select & Better: Selection of more uniform wood grain with slight variations in natural shading Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. Character floors: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 					
Color choice (refer to 2019 Mirage Collections)	51 colors: Nordic, Greystone, Charcoal, Graphite, Isla, Cape Cod, Rio, Savanna, Rich Oak, Havana, Java, Coffee, Sierra, Golden, Nevada, Auburn, Canyon, Umbria, Vienna, Platinum, Natural, Brass, Onyx, White Mist, Snowdrift, Sand Dune, Grey Drizzle, Lunar Eclipse, Nightfall, Bubble Bath, Hula Hoop, Carousel, Sand Castle, Château, Roller Coaster, Gelato, Treasure, Peppermint, Hopscootch, Nougat, Tree House, Praline, Gingerbread, Black Jelly Bean, Driftwood, Rock Cliff, Barn Wood, Papyrus, Seashell, Sandstone, Fossil. Some products may not be available. Ask your Mirage representative or consult the product chart.					
Finish	<ul style="list-style-type: none"> DuraMatt™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. Nanolinx™ HD: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> Semi-gloss (50% gloss) or Cashmere®* (18% gloss) Nanolinx™ Commercial: Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55					
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species) SD (Smoke Development) 75 to 400 (depends on wood species) 			Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSV (Flame Spread Value) 100 to 150 (depends on wood species) SD (Smoke Development) 200 to 300 (depends on wood species) 		
	Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species)			R value: R 0.3 to 0.4 (depends on wood species)		
	Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Engineered) conform					
Provenance	Made in St-Georges, Qc, Canada.					
Use	Residential, light commercial or commercial (Nanolinx™ Commercial)					
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Multifunction Reducer, Threshold, "T" molding, Quarter round					
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (For the glued down and nailed/stapled installation relative humidity must be maintained within a range of 25% and 70% and for the floated installation relative humidity must be maintained between 30% and 60%). 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications with Nanolinx™ Commercial 					
Packaging	2-9/16"	3-5/16"	5"	6-1/2"	7-3/4"	
Content of a box	• 20 ft ²	• 25 ft ²	• 34.10 ft ²	• 22.15 ft ²	• 17.60 ft ²	
Size of a box	• 48" L x 8-1/4" W x 3-1/4" H	• 47" L x 10-1/4" W x 3-1/4" H	• 83" L x 10-1/2" W x 3-1/4" H	• 83" L x 7" W x 3-1/4" H	• 83" L x 8-3/8" W x 3-1/4" H	
Weight of a box	• 27 to 34 lbs	• 34 to 41 lbs	• 65 to 70 lbs	• 42 to 45 lbs	• 50 to 53 lbs	
Content of a pallet	• 50 boxes = 1 000 ft ² (5 boxes/W x 10 boxes/H)	• 40 boxes = 1 000 ft ² (4 boxes/W x 10 boxes/H)	• 32 boxes = 1 091.2 ft ² (4 boxes/W x 8 boxes/H)	• 48 boxes = 1 063.2 ft ² (6 boxes/W x 8 boxes/H)	• 50 boxes = 880 ft ² (5 boxes/W x 10 boxes/H)	
Size of a pallet	• 48" L x 42" W x 37" H	• 47" L x 42" W x 37" H	• 83" L x 42" W x 30" H	• 83" L x 42" W x 30" H	• 83" L x 42" W x 36" H	
Relative species hardness						
NWFA Janka Test	<ul style="list-style-type: none"> Walnut 1,010 lbs - 22% softer Yellow Birch 1,260 lbs - 2% softer Red Oak 1,290 lbs - average hardness Sapele 1,300 lbs - 1% harder African Mahogany 1,300 lbs - 1% harder White Oak 1,360 lbs - 5% harder Maple 1,450 lbs - 12% harder Hickory 1,820 lbs - 41% harder Brazilian Cherry 2,350 lbs - 82% harder 					
Hardness test (ASTM-D-143)						
Red Oak 1290 lbs* - 100%						
*lbs = Applied force in pounds						

* Cashmere is a registered trademark used under license.

** For floated installation please review technical newsletter #25 available on Mirage website in the Guide and support section (except for 6-1/2" for Maple and Hickory species).



Characteristics	Mirage Engineered														
	Herringbone Collection														
Description	<ul style="list-style-type: none"> Engineered prefinished hardwood flooring with tongue and groove edges, and grooves at both ends Micro-V bevel (on 4 sides) 														
Thickness	3/8" (Sawn hardwood layer 5/32", 5-ply plywood base 15/64")	1/2" (Sawn hardwood layer 5/32", 7-ply plywood base 11/32")													
Width	2-9/16"	5"													
Length	17-7/8"	20"													
Installation	Glued down (above, on or below grade)														
Subfloor	Wood, concrete or radiant heat system (with the exception of Hickory)														
Species	5 species: Maple, Red Oak, White Oak, Hickory Character, Walnut Character														
Grade	<ul style="list-style-type: none"> Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. Character floors: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 														
Color choice (refer to 2019 Mirage Collections)	33 colors: Nordic, Greystone, Charcoal, Graphite, Cape Cod, Rio, Savanna, Rich Oak, Havana, Java, Coffee, Sierra, Golden, Nevada, Auburn, Canyon, Umbria, Vienna, Platinum, Natural, White Mist, Snowdrift, Sand Dune, Grey Drizzle, Lunar Eclipse, Nightfall, Bubble Bath, Hula Hoop, Sand Castle, Roller Coaster, Gelato, Peppermint, Hopscotch.														
Finish	<ul style="list-style-type: none"> DuraMatt™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. Nanolinx™ HD: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> Semi-gloss (50% gloss) or Cashmere®* (18% gloss) Nanolinx™ Commercial: Ultraresistant finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55														
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> FSI (Flame Spread Index) 100 to 150 Classe C (depends on wood species) SD (Smoke Development) 75 to 400 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species)	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> FSV (Flame Spread Value) 100 to 150 (depends on wood species) SD (Smoke Development) 200 to 300 (depends on wood species) R value: R 0.3 to 0.4 (depends on wood species)													
	Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Engineered) conform														
Provenance	Made in St-Georges, Qc, Canada.														
Use	Residential, light commercial or commercial (Nanolinx™ Commercial)														
Accessory	Round Stair nosing, Square Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round														
Warranty	<ul style="list-style-type: none"> Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 25% and 70%). 35-year finish warranty for residential applications 3-year finish warranty for light commercial applications 5-year finish warranty for commercial applications 														
Patterns	Length: 17-7/8"	Length: 20"													
	<ul style="list-style-type: none"> Herringbone Basket Double Herringbone Cube English pattern (bricks) Fence 	<ul style="list-style-type: none"> Herringbone Basket Double Herringbone Cube English pattern (bricks) Fence 													
Packaging	Length: 17-7/8"	Length: 20"													
Content of a box	• 15,28 ft ²	• 25 ft ²													
Size of a box	• 37" L x 8-1/4" W x 3-1/4" H	• 61" L x 10-1/2" W x 3-1/4" H													
Weight of a box	• 22 to 27 lbs	• 46 to 51 lbs													
Content of a pallet	• 40 boxes = 611.2 ft ² (5 boxes/W x 8 boxes/H)	• 40 boxes = 1000 ft ² (5 boxes/W x 8 boxes/H)													
Size of a pallet	• 42" L x 37" W x 30" H	• 61" L x 42" W x 37" H													
Relative species hardness	<table border="0"> <tr> <td>NWFA Janka Test</td> <td>• Walnut</td> <td>1,010 lbs - 22% softer</td> </tr> <tr> <td rowspan="2">Hardness test (ASTM-D-143)</td> <td>• Red Oak</td> <td>1,290 lbs - average hardness</td> </tr> <tr> <td>• White Oak</td> <td>1,360 lbs - 5% harder</td> </tr> <tr> <td rowspan="2">Red Oak 1290 lbs* - 100%</td> <td>• Maple</td> <td>1,450 lbs - 12% harder</td> </tr> <tr> <td>• Hickory</td> <td>1,820 lbs - 41% harder</td> </tr> </table> *lbs = Applied force in pounds		NWFA Janka Test	• Walnut	1,010 lbs - 22% softer	Hardness test (ASTM-D-143)	• Red Oak	1,290 lbs - average hardness	• White Oak	1,360 lbs - 5% harder	Red Oak 1290 lbs* - 100%	• Maple	1,450 lbs - 12% harder	• Hickory	1,820 lbs - 41% harder
NWFA Janka Test	• Walnut	1,010 lbs - 22% softer													
Hardness test (ASTM-D-143)	• Red Oak	1,290 lbs - average hardness													
	• White Oak	1,360 lbs - 5% harder													
Red Oak 1290 lbs* - 100%	• Maple	1,450 lbs - 12% harder													
	• Hickory	1,820 lbs - 41% harder													

* Cashmere is a registered trademark used under license.



Characteristics	Mirage Lock						
Description	<ul style="list-style-type: none"> • For Admiration, Natural, Exotic and Sweet Memories Collections • Floated Engineered prefinished hardwood flooring • Rightloc™ locking system • Incomparable tongue and groove fit for remarkable uniformity • Micro-V bevel (on 4 sides) 						
Thickness	7/16" (Sawn hardwood layer 5/64", HDF Core 9/32" and wood backing board)						
Width	4-5/16"						
Length	Lengths from 14" to 46"						
Installation	Floated over a recommended membrane (above, on or below grade)						
Subfloor	Wood, concrete or radiant heat system						
Species	4 species: Maple, Red Oak, African Mahogany and Sapele.						
Grade	<ul style="list-style-type: none"> • Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a range of color variation. • Character floors: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment. 						
Color choice (refer to 2019 Mirage Collections)	<p>32 colors: Nordic, Greystone, Charcoal, Graphite, Cape Cod, Rio, Savanna, Rich Oak, Havana, Java, Coffee, Sierra, Golden, Nevada, Auburn, Canyon, Umbria, Vienna, Platinum, Natural, Brass, Onyx, Château, Gelato, Treasure, Peppermint, Hopscotch, Nougat, Tree House, Praline, Gingerbread, Black Jelly Bean</p> <p>Some products may not be available. Ask your Mirage representative or consult the product chart.</p>						
Finish	<ul style="list-style-type: none"> • DuraMatt™: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. • Nanolinx™ HD: Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> • Semi-gloss (50% gloss) or Cashmere®* (18% gloss) <p>UV Protection: All products</p> <p>Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5</p>						
Applicable standards	<table border="0"> <tr> <td> Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 85 to 110 Classe C (depends on wood species) • SD (Smoke Development) 220 to 240 (depends on wood species) </td> <td> Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 85 to 90 (depends on wood species) • SD (Smoke Development) 305 to 365 (depends on wood species) </td> </tr> <tr> <td> Critical radiant flux (ASTM-E-648-94a): 0.46 to 0.47 watt/cm² (depends on wood species) </td> <td> R value: R 0.34 to 0.36 (depends on wood species) </td> </tr> <tr> <td colspan="2"> Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Lock) conform </td> </tr> </table>	Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 85 to 110 Classe C (depends on wood species) • SD (Smoke Development) 220 to 240 (depends on wood species)	Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 85 to 90 (depends on wood species) • SD (Smoke Development) 305 to 365 (depends on wood species)	Critical radiant flux (ASTM-E-648-94a): 0.46 to 0.47 watt/cm ² (depends on wood species)	R value: R 0.34 to 0.36 (depends on wood species)	Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Lock) conform	
Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 85 to 110 Classe C (depends on wood species) • SD (Smoke Development) 220 to 240 (depends on wood species)	Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 85 to 90 (depends on wood species) • SD (Smoke Development) 305 to 365 (depends on wood species)						
Critical radiant flux (ASTM-E-648-94a): 0.46 to 0.47 watt/cm ² (depends on wood species)	R value: R 0.34 to 0.36 (depends on wood species)						
Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group (Lock) conform							
Provenance	Made in St-Georges, Qc, Canada.						
Use	Residential or light commercial						
Accessory	Round Stair nosing, Round Reducer, Threshold, "T" molding, Quarter round and membrane						
Warranty	<ul style="list-style-type: none"> • Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 30% and 60%) • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications 						
Packaging	4-5/16"						
Content of a box	• 22 ft ²						
Size of a box	• 48" L x 9-1/2" W x 3-3/4" H						
Weight of a box	• 45 lbs						
Content of a pallet	• 40 boxes = 880 ft ² (4 boxes/W x 10 boxes/H)						
Size of a pallet	• 48" L x 38" W x 40" H						
Relative species hardness							
NWFA Janka Test	<ul style="list-style-type: none"> • Red Oak 1,290 lbs - average hardness • African Mahogany 1,300 lbs - 1% harder • Sapele 1,300 lbs - 1% harder • Maple 1,450 lbs - 12% harder 						
Hardness test (ASTM-D-143)							
Red Oak 1290 lbs* - 100%							
*lbs = Applied force in pounds							

* Cashmere is a registered trademark used under license.